

Title (en)
Dry cleaner

Title (de)
Trockenreiniger

Title (fr)
Nettoyeur à sec

Publication
EP 1923500 A3 20091230 (EN)

Application
EP 07022222 A 20071115

Priority
JP 2006313317 A 20061120

Abstract (en)
[origin: EP1923500A2] According to the present invention, a highly safe dry cleaner is provided, which ensures safety without the danger of ignition in a drying process even if so-called microcomputer runaway occurs. The dry cleaner includes a relay sequence controlling circuit (71). The relay sequence controlling circuit (71) includes a serial connection of a first valve (V27) to be controlled, a first switch (77) which controls the turn-on of the first valve (V27) and a second contact (76a) provided in a second relay (76). A detection circuit (79) which controls the second contact (76a) is connected to the serial connection. Thus, the first valve (V27) is maintained in an inactive state irrespective of a first switch turn-on control performed by a control section (81) until the detection circuit (79) performs a predetermined operation to turn on the second contact 76a.

IPC 8 full level
D06F 43/00 (2006.01)

CPC (source: EP US)
D06F 43/00 (2013.01 - EP US)

Citation (search report)
• [A] WO 03062517 A1 20030731 - NARDINI GIAN VIERI [IT]
• [A] US 2142042 A 19381227 - BOWDOIN GEORGE E, et al
• [A] US 5367787 A 19941129 - IKEDA TOMOHIKO [JP], et al

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA HR MK RS

DOCDB simple family (publication)
EP 1923500 A2 20080521; EP 1923500 A3 20091230; CN 100594268 C 20100317; CN 101187144 A 20080528; JP 2008125745 A 20080605;
JP 4901434 B2 20120321; US 2008115540 A1 20080522

DOCDB simple family (application)
EP 07022222 A 20071115; CN 200710152787 A 20070921; JP 2006313317 A 20061120; US 98414807 A 20071114