

Title (en)
WIRE DEPOSITING APPARATUS

Title (de)
VORRICHTUNG ZUM ABLEGEN VON DRAHT

Title (fr)
ENFUTEUR POUR FIL METALLIQUE

Publication
EP 1926673 A1 20080604 (FR)

Application
EP 06776426 A 20060726

Priority
• EP 2006007379 W 20060726
• IT VI20050215 A 20050728

Abstract (en)
[origin: WO2007012476A1] The invention concerns an apparatus (1) for depositing wire (11), of the type providing for deposition of the wire, such as welding wire, steel wire with low carbon content, stainless steel wire, core wire or aluminum wire wrapped in a loop, inside an depositing apparatus (20). Said wire depositing apparatus consists essentially of two parts and more precisely a first part (2) wherein are positioned the capstans for driving and drawing the wire, as well as a device (10), called flyer, which provides for depositing and winding the wire inside the depositing apparatus. By contrast, in the second part (3) of the depositing apparatus, is set and manipulated the depositing apparatus to be filled with the wound wire. Said depositing apparatus is characterized in that the flyer is provided, besides a rotational movement about its vertical axis, a vertical reciprocating rectilinear movement.

IPC 8 full level
B65H 54/80 (2006.01); **B21C 47/14** (2006.01)

CPC (source: EP KR US)
B21C 47/14 (2013.01 - KR); **B21C 47/143** (2013.01 - EP US); **B65H 54/80** (2013.01 - KR)

Citation (search report)
See references of WO 2007012476A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
DE 202006006648 U1 20060727; EP 1926673 A1 20080604; IT VI20050215 A1 20070129; KR 101244522 B1 20130318; KR 20080038315 A 20080506; NO 20080623 L 20080314; US 2010127111 A1 20100527; US 7971819 B2 20110705; WO 2007012476 A1 20070201

DOCDB simple family (application)
DE 202006006648 U 20060421; EP 06776426 A 20060726; EP 2006007379 W 20060726; IT VI20050215 A 20050728; KR 20087002319 A 20060726; NO 20080623 A 20080204; US 98914906 A 20060726