

Title (en)

Formwork dummy designed for the creation of openings, in particular for concrete work

Title (de)

Schalung zum Aussparen von Öffnungen, insbesondere für Beton-Bauten

Title (fr)

Mannequin de coffrage destiné à la réalisation d'ouvertures, notamment pour les ouvrages en béton

Publication

**EP 1930528 B1 20100210 (FR)**

Application

**EP 07356171 A 20071129**

Priority

FR 0610525 A 20061201

Abstract (en)

[origin: EP1930528A1] The model (1) has a lower frame (2) and an upper frame (3) formed of horizontal elements (4) and vertical elements (5) both fixed to each other by vertical arms (6) and horizontal arms (7). The vertical and horizontal arms are arranged with respect to each other to form bars of seal cleats (9), in reinforcement gusset angle (8), on circumference of peripheral plates (10), where the plates are fixed on outer edges of the elements forming the frames.

IPC 8 full level

**E04G 15/02** (2006.01)

CPC (source: EP)

**B28B 7/28** (2013.01); **E04G 15/02** (2013.01); **B28B 7/186** (2013.01)

Cited by

FR2979367A1; FR2952097A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 1930528 A1 20080611; EP 1930528 B1 20100210;** AT E457393 T1 20100215; DE 602007004701 D1 20100325; ES 2340731 T3 20100608; FR 2909399 A1 20080606; FR 2909399 B1 20090213; PL 1930528 T3 20100730; PT 1930528 E 20100423

DOCDB simple family (application)

**EP 07356171 A 20071129;** AT 07356171 T 20071129; DE 602007004701 T 20071129; ES 07356171 T 20071129; FR 0610525 A 20061201; PL 07356171 T 20071129; PT 07356171 T 20071129