

Title (en)
Demodulating video broadcast signals

Title (de)
Demodulierung von Videoausstrahlungssignalen

Title (fr)
Démodulation de signaux de diffusion vidéo

Publication
EP 1933516 A2 20080618 (EN)

Application
EP 08000336 A 19980501

Priority

- EP 98303446 A 19980501
- GB 9709063 A 19970502
- US 5419597 P 19970730
- GB 9727112 A 19971222
- GB 9727113 A 19971222
- GB 9808989 A 19980427
- GB 9808993 A 19980427
- GB 9808990 A 19980427
- GB 9808991 A 19980427
- GB 9808992 A 19980427

Abstract (en)
A demodulator suitable for implementation in a single chip for demodulating digital video broadcast signals comprising data modulated on a multiplicity of spaced carrier frequencies, wherein an input broadcast signal is converted to a frequency sufficiently low to enable analog digital conversion of the signal, the demodulator comprising analog to digital conversion means (20) for converting the broadcast signal to a series of digital samples, real to complex conversion means (22) for converting each digital sample to a complex number value, Fourier transform means (24) for analysing the complex number values to provide a series of signal values for each carrier frequency, frequency control means (9, 3 8), comprising means responsive to the output of said Fourier Transform means for producing a signal for controlling the frequency of the signal formed by said complex number values, and signal processing means for receiving the signal values and providing an output for decoding, the signal processing means including channel equalisation means (32) and channel state information generating means (34). Other arrangements are concerned with automatic frequency control for example based on coarse frequency control means for controlling the frequency in terms of increments of the carrier spacing frequency, and fine frequency control means for controlling the frequency for values less than a single carrier spacing frequency interval. Still other arrangements are concerned with timing synchronisation means for synchronising the Fourier Transform means with the symbol periods of the broadcast signal. Further arrangements are concerned with phase error correction, for example based on determining the variation in phase of continual pilot signals between consecutive symbols in the broadcast signals.

IPC 8 full level
H04L 27/26 (2006.01); **H04L 1/00** (2006.01); **H04L 25/03** (2006.01); **H04N 5/00** (2011.01); **H04N 5/455** (2006.01); **H04N 7/24** (2011.01); **H04L 27/00** (2006.01)

CPC (source: EP)
H04L 1/004 (2013.01); **H04L 25/03025** (2013.01); **H04L 27/2659** (2013.01); **H04L 27/266** (2013.01); **H04L 27/2663** (2013.01); **H04L 27/2665** (2013.01); **H04L 27/2679** (2013.01); **H04N 5/455** (2013.01); **H04N 21/2383** (2013.01); **H04N 21/4263** (2013.01); **H04N 21/4382** (2013.01); **H04N 21/6112** (2013.01); **H04L 1/0059** (2013.01); **H04L 27/2607** (2013.01); **H04L 2027/0028** (2013.01); **H04L 2027/0067** (2013.01); **H04L 2027/0087** (2013.01)

Citation (applicant)

- GB 2307155 A 19970514 - BRITISH BROADCASTING CORP [GB]
- GB 2037155 A 19800709 - POLY SAKS APS
- STOTT, J.H.: "Explaining Some of the Magic of COFDM", PROCEEDINGS OF 20TH INTERNATIONAL TELEVISION SYMPOSIUM, June 1997 (1997-06-01)

Cited by
EP2566123A3; US10256929B2; US8761326B2

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1933516 A2 20080618; EP 1933516 A3 20090304

DOCDB simple family (application)
EP 08000336 A 19980501