

Title (en)

Method of driving plasma display panel

Title (de)

Ansteuerverfahren für eine Plasmaanzeigetafel

Title (fr)

Procédé de commande d'un panneau d'affichage à plasma

Publication

**EP 1939844 A1 20080702 (EN)**

Application

**EP 06292071 A 20061229**

Priority

EP 06292071 A 20061229

Abstract (en)

A method of driving a plasma display panel is disclosed. The method including a scan electrode, a sustain electrode, and a barrier rib includes applying a scan pulse of a positive polarity to the scan electrode for an address period, and applying a data pulse of a negative polarity corresponding to the scan pulse of the positive polarity to the address electrode for the address period. A gap between the scan electrode and the sustain electrode positioned within a discharge cell partitioned by the barrier rib is more than a height of the barrier rib.

IPC 8 full level

**G09G 3/288** (2006.01); **G09G 3/293** (2013.01)

CPC (source: EP)

**G09G 3/2932** (2013.01); **H01J 11/12** (2013.01); **H01J 11/24** (2013.01); **H01J 11/32** (2013.01); **G09G 2320/0228** (2013.01);  
**H01J 2211/323** (2013.01); **H01J 2211/326** (2013.01)

Citation (search report)

- [Y] EP 1477958 A2 20041117 - THOMSON PLASMA SAS [FR]
- [Y] US 6411268 B1 20020625 - NAKAMURA TADASHI [JP], et al
- [Y] EP 1455332 A2 20040908 - LG ELECTRONICS INC [KR]
- [Y] EP 0790597 A1 19970820 - MATSUSHITA ELECTRIC IND CO LTD [JP]
- [A] EP 1244088 A2 20020925 - FUJITSU LTD [JP]
- [A] US 2003034937 A1 20030220 - KIM JUNG HUN [KR]

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA HR MK RS

DOCDB simple family (publication)

**EP 1939844 A1 20080702**

DOCDB simple family (application)

**EP 06292071 A 20061229**