

Title (en)

IMPROVED CARBON DIOXIDE NANOSENSOR, AND RESPIRATORY CO<sub>2</sub> MONITORS

Title (de)

VERBESSERTER KOHLENSTOFFDIOXID-NANOSENSOR SOWIE ATEM-CO<sub>2</sub>-ÜBERWACHUNGSGERÄTE

Title (fr)

NANODÉTECTEUR DE DIOXYDE DE CARBONE PERFECTIONNÉ ET MONITEURS DU CO<sub>2</sub> RESPIRATOIRE

Publication

**EP 1941270 A2 20080709 (EN)**

Application

**EP 06851621 A 20060718**

Priority

- US 2006028079 W 20060718
- US 70094405 P 20050720
- US 73090505 P 20051027
- US 77313806 P 20060213
- US 39049306 A 20060327
- US 43727506 A 20060518

Abstract (en)

[origin: WO2008039165A2] An electronic system and method for detecting analytes, such as carbon dioxide, is provided, using an improved nanostructure sensor (CO<sub>2</sub> sensor). The CO<sub>2</sub> sensor may comprise a substrate and a nanostructure, such as a one or more carbon nanotubes disposed over the substrate (e.g., as a network). One or more conductive elements may electrically communicate with the nanostructure. A counter or gate electrode may be positioned adjacent the nanostructure. A functionalization material reactive with carbon dioxide may be included, either disposed in contact with the nanostructure or isolated by a dielectric. The sensor may be connected to a circuit responsive to changes in CO<sub>2</sub> concentration in the environment. Embodiments are described of medical sensing systems including one or more CO<sub>2</sub> sensors. One embodiment comprises a breath sampling cannula which is connected to a sensor unit. In an alternative, the cannula permits supplemental oxygen to be administered, while recovering and measuring analytes in breath samples. The cannula may connect to a portable processor-display unit for monitoring one or more analytes, such as CO<sub>2</sub>. Another embodiment includes a cannula configured for the monitoring of sleep disorders, such as apnea, comprising one or more sensors disposed adjacent a breath sampling channel, optionally including flow rate or other sensors. The sensors may be connected by wired or wireless links for to a processor/input/display unit. Any of the embodiments may include filters, selectively permeable membranes, absorbents, and the like to precondition the breath sample, may be configured to include complementary chemistry measurements.

IPC 8 full level

**C12M 3/00** (2006.01); **C12Q 1/68** (2006.01); **G01N 21/00** (2006.01); **G01N 27/00** (2006.01); **G01N 27/12** (2006.01); **G01N 33/00** (2006.01); **G01N 33/543** (2006.01)

CPC (source: EP)

**B82Y 30/00** (2013.01); **G01N 27/4146** (2013.01); **G01N 33/004** (2013.01); **G01N 33/497** (2013.01)

Cited by

US7522040B2; US7547931B2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA HR MK RS

DOCDB simple family (publication)

**WO 2008039165 A2 20080403**; **WO 2008039165 A3 20080807**; EP 1941270 A2 20080709; EP 1941270 A4 20110316

DOCDB simple family (application)

**US 2006028079 W 20060718**; EP 06851621 A 20060718