

Title (en)  
DETENT ESCAPEMENT FOR A TIMEPIECE

Title (de)  
ARRETIERUNGSCHEMMUNG FÜR EINE UHR

Title (fr)  
ECHAPPEMENT A DETENTE POUR PIECE D'HORLOGERIE

Publication  
**EP 1941326 A2 20080709 (FR)**

Application  
**EP 06806882 A 20060929**

Priority  
• EP 2006066884 W 20060929  
• EP 05109056 A 20050930  
• EP 06806882 A 20060929

Abstract (en)  
[origin: EP1770452A1] The escapement has an escape wheel (1) pivoted on an axis (X1), and a balance pivoted on an axis (X2). A detent (11) is pivoted on an axis (X3) and supports a pallet lock (21) interacting with a tooth of an escape wheel along a length of penetration to block the wheel in an idle phase over a course of which a balance exerts a free arc of oscillation. An impulse pallet (7) interacts with another tooth of the escape wheel, when the detent is pivoted for freeing the escape wheel. The teeth are placed on both sides of center lines (L) joining the axes (X1, X2) in the idle phase.

IPC 8 full level  
**G04B 15/06** (2006.01)

CPC (source: EP US)  
**G04B 15/06** (2013.01 - EP US); **G04B 17/063** (2013.01 - EP US)

Citation (search report)  
See references of WO 2007039558A2

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 1770452 A1 20070404**; AT E429666 T1 20090515; CN 101278240 A 20081001; CN 101278240 B 20100602;  
DE 602006006464 D1 20090604; EP 1941326 A2 20080709; EP 1941326 B1 20090422; ES 2326340 T3 20091007; HK 1118344 A1 20090206;  
JP 2009510425 A 20090312; JP 4898814 B2 20120321; RU 2008117152 A 20091110; RU 2408042 C2 20101227; US 2008219103 A1 20080911;  
US 7458717 B2 20081202; WO 2007039558 A2 20070412; WO 2007039558 A3 20070628

DOCDB simple family (application)  
**EP 05109056 A 20050930**; AT 06806882 T 20060929; CN 200680036057 A 20060929; DE 602006006464 T 20060929;  
EP 06806882 A 20060929; EP 2006066884 W 20060929; ES 06806882 T 20060929; HK 08109738 A 20080902; JP 2008532792 A 20060929;  
RU 2008117152 A 20060929; US 8824206 A 20060929