

Title (en)

Method of driving plasma display panel

Title (de)

Ansteuerverfahren für eine Plasmaanzeigetafel

Title (fr)

Procédé de commande d'un panneau d'affichage à plasma

Publication

**EP 1942483 A1 20080709 (EN)**

Application

**EP 07290003 A 20070103**

Priority

EP 07290003 A 20070103

Abstract (en)

A method of driving a plasma display panel is disclosed. According to a negative sustain driving method for a plasma display panel using a negative sustain voltage, the negative sustain voltage and the ground level voltage are alternately applied to each of scan electrode Y and sustain electrode Z in a sustain period, and the negative sustain voltage is first applied to the sustain electrode Z.

IPC 8 full level

**G09G 3/28** (2006.01); **G09G 3/288** (2006.01); **G09G 3/292** (2013.01); **G09G 3/294** (2013.01)

CPC (source: EP)

**G09G 3/2927** (2013.01); **G09G 3/294** (2013.01); **G09G 2320/0242** (2013.01); **G09G 2330/021** (2013.01)

Citation (search report)

- [XY] US 6072279 A 20000606 - SHINO TAICHI [JP], et al
- [X] EP 1647965 A2 20060419 - LG ELECTRONICS INC [KR]
- [T] US 2007046582 A1 20070301 - PAIK DONGKI [KR], et al
- [T] EP 1752952 A1 20070214 - LG ELECTRONICS INC [KR]
- [Y] KIM H ET AL: "Firing and Sustaining Discharge Characteristics in Alternating Current Microdischarge Cell With Three Electrodes", IEEE TRANSACTIONS ON PLASMA SCIENCE, IEEE SERVICE CENTER, PISCATAWAY, NJ, US, vol. 32, no. 2, April 2004 (2004-04-01), pages 488 - 492, XP011114572, ISSN: 0093-3813

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA HR MK RS

DOCDB simple family (publication)

**EP 1942483 A1 20080709**

DOCDB simple family (application)

**EP 07290003 A 20070103**