

Title (en)
ACRYLIC CAPSTOCK

Title (de)
ACRYLDECKSCHICHT

Title (fr)
CAPSTOCK ACRYLIQUE

Publication
EP 1948441 A1 20080730 (FR)

Application
EP 05822986 A 20051125

Priority
• FR 2005002930 W 20051125
• FR 2005002855 W 20051117

Abstract (en)
[origin: WO2007057525A1] The invention relates to a method for protecting a plastic structure consisting in superimposing by coextrusion, hot compression and by multiple injections a PMMA-containing protective layer (I), possibly a pigmented layer (II) and an intermediate ductile layer (III) comprising a sequence copolymer of formula BA_n consisting of a block polymer B comprising at least 60 % by weight of at least one type of (meth)acrylic monomer whose T_g is less than 5 °C, n blocks of polymer A which are bound to the polymer B block by covalent bonds, wherein n is an integer ranging from 1 to 10, and comprise at least 60 % by weight of at least one type of (meth)acrylic monomer whose T_g is greater than 0 °C, and a structured plastic layer (IV).

IPC 8 full level
B32B 27/30 (2006.01)

CPC (source: EP US)
B32B 27/08 (2013.01 - US); **B32B 27/30** (2013.01 - EP); **B32B 27/302** (2013.01 - US); **B32B 27/304** (2013.01 - US); **B32B 27/308** (2013.01 - US); **B32B 2307/4026** (2013.01 - US); **B32B 2327/06** (2013.01 - US); **B32B 2333/12** (2013.01 - US); **B32B 2355/02** (2013.01 - US)

Citation (search report)
See references of WO 2007057525A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 2007057525 A1 20070524; EP 1948441 A1 20080730

DOCDB simple family (application)
FR 2005002930 W 20051125; EP 05822986 A 20051125