

Title (en)

METHOD AND DEVICE IN WEB WINDING IN CONNECTION WITH THE SET CHANGE OF A SLITTER-WINDER

Title (de)

VERFAHREN UND VORRICHTUNG ZUM WICKELN VON BAHNEN IN VERBINDUNG MIT DEM SATZWECHSEL EINES LÄNGSSCHNEIDE-WICKLERS

Title (fr)

PROCEDE ET DISPOSITIF D'ENROULEMENT DE NAPPES ASSOCIES A LA MODIFICATION DU REGLAGE D'UNE BOBINEUSE-REFENDEUSE

Publication

EP 1954614 A2 20080813 (EN)

Application

EP 06820091 A 20061123

Priority

- FI 2006050511 W 20061123
- FI 20055628 A 20051128

Abstract (en)

[origin: WO2007060293A3] The invention relates to a method in winding a fibre web in connection with the set change of a slitter-winder, in which method the fibre web (W) is wound in a carrier roll windup, in which partial webs (W) wound by the slitter-winder are wound to web rolls (10) carried by a front carrier roll (11) and a rear carrier roll (12, 13, 14) around cores. In the method, cores are fed to the slitter-winder as an array for the set change. For the time of the set change i.e. for removing completed rolls (10) and starting new rolls (10), the winding is stopped. The web is cut by a cutting blade (15), the tails of partial webs are fastened to web rolls, completed partial web rolls are removed by means of a roll pusher (17) and new cores are transferred to the support of the carrier rolls (11, 12, 13, 14). In the method, when removing the completed partial web roll (10) from the slitter-winder by the roll pusher (17), the main tail part of a glue stripe formed by glue applied to the end of the web is pressed finally fast in a nip between the roll pusher (17) and the partial web roll (10). The invention relates also to a device in winding a fibre web in connection with the set change of a slitter-winder, which device is arranged into connection with a carrier roll windup, which carrier roll windup comprises a rear carrier roll (11) and a front carrier roll (12, 13, 14), carried by which the partial webs cut to partial webs by the slitter-winder are wound to partial web rolls around winding tubes (20) i.e. cores. The device comprises a roll pusher (17), which roll pusher (17) is pivoted into connection with the windup so that the pusher (17) is arranged to push the roll (10) out of the windup forming a nip between the roll pusher (17) and the completed partial web roll (10) for the final compression of the glue stripe applied to the tail of the partial web roll.

IPC 8 full level

B65H 19/29 (2006.01); **B65H 19/22** (2006.01)

IPC 8 main group level

B65H (2006.01)

CPC (source: EP FI)

B65H 19/2246 (2013.01 - EP FI); **B65H 19/29** (2013.01 - EP); **B65H 19/30** (2013.01 - FI); **B65H 2301/4148** (2013.01 - EP)

Cited by

EP2543616A1; US8870112B2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

WO 2007060293 A2 20070531; **WO 2007060293 A3 20070823**; AT E527197 T1 20111015; CN 101316779 A 20081203; CN 101316779 B 20121003; EP 1954614 A2 20080813; EP 1954614 B1 20111005; FI 118762 B 20080314; FI 20055628 A0 20051128; FI 20055628 A 20070529

DOCDB simple family (application)

FI 2006050511 W 20061123; AT 06820091 T 20061123; CN 200680044459 A 20061123; EP 06820091 A 20061123; FI 20055628 A 20051128