

Title (en)

Method for coating a printing machine cylinder

Title (de)

Verfahren zum Beschichten eines Druckmaschinenzylinders

Title (fr)

Procédé destiné au revêtement d'un cylindre d'une machine d'impression

Publication

**EP 1955864 A3 20100609 (DE)**

Application

**EP 08002323 A 20080208**

Priority

DE 102007006705 A 20070210

Abstract (en)

[origin: EP1955864A2] The method involves providing a printing press cylinder with a metallic cylinder basic body, which includes an outer surface area and a lockup slot. A coating containing nickel is applied to the basic body in a region of the outer surface area and in a region of the lockup slot by autocatalytic and/or chemical deposition. An alloy containing nickel and phosphorous is applied to the cylinder basic body by the autocatalytic and/or chemical deposition. The autocatalytic and/or chemical deposition takes place such that the applied coating containing nickel has a thickness of 15-50 micrometers.

IPC 8 full level

**B41N 7/00** (2006.01)

CPC (source: EP US)

**B41F 13/10** (2013.01 - EP US); **B41F 13/193** (2013.01 - EP US); **B41N 7/005** (2013.01 - EP US); **B41N 2207/02** (2013.01 - EP US); **B41N 2207/10** (2013.01 - EP US)

Citation (search report)

- [XDI] DE 10349446 A1 20050602 - KOENIG & BAUER AG [DE]
- [A] US 4643095 A 19870217 - PFIZENMAIER WOLFGANG [DE], et al
- [A] DE 10355005 A1 20040624 - KOENIG & BAUER AG [DE]

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

**EP 1955864 A2 20080813**; **EP 1955864 A3 20100609**; DE 102007006705 A1 20080814; US 2008190310 A1 20080814

DOCDB simple family (application)

**EP 08002323 A 20080208**; DE 102007006705 A 20070210; US 2857008 A 20080208