

Title (en)

METHOD AND DEVICE FOR GRAVURE PRINTING USING AN ERASABLE AND RE-USABLE PRINTING FORM

Title (de)

VERFAHREN UND VORRICHTUNG FÜR DEN TIEFDRUCK MITTELS EINER LÖSCH- UND WIEDER VERWENDBAREN TIEFDRUCKFORM

Title (fr)

PROCEDE ET DISPOSITIF D'HELIOGRAVURE AU MOYEN D'UNE FORME EN CREUX EFFACABLE ET REUTILISABLE

Publication

EP 1957286 A1 20080820 (DE)

Application

EP 06806577 A 20061027

Priority

- EP 2006010360 W 20061027
- DE 102005052156 A 20051102

Abstract (en)

[origin: DE102005052156A1] The method involves a basic grid designed on the maximal color quantity. The impression of the basic grid of the gravure blank shape are simultaneously filled with a filling material by an applicator for forming printing block in the filling process, then in an artwork process the filling material is pictorially removed by thermal ablation by means of a pixel-transmitting device from the impressions. The pictorially grid gravure is dyed and then printed in the gravure. Independent claims are included for following: (1) Device for gravure print by means of detachable and reusable gravure cylinder; (2) Method for manufacturing of basic grid; and (3) Filling material for filling of basic grid.

IPC 8 full level

B41N 1/06 (2006.01); **B41N 3/00** (2006.01)

CPC (source: EP US)

B41N 1/06 (2013.01 - EP US); **B41N 3/003** (2013.01 - EP US)

Citation (search report)

See references of WO 2007051565A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

DE 102005052156 A1 20070503; CA 2628155 A1 20070510; CA 2628155 C 20110510; CN 101365595 A 20090211; EP 1957286 A1 20080820; JP 2009514695 A 20090409; US 2009126586 A1 20090521; WO 2007051565 A1 20070510

DOCDB simple family (application)

DE 102005052156 A 20051102; CA 2628155 A 20061027; CN 200680041072 A 20061027; EP 06806577 A 20061027; EP 2006010360 W 20061027; JP 2008538290 A 20061027; US 8439106 A 20061027