

Title (en)

TRUING DEVICE AND TRUING METHOD FOR GRINDING WHEEL

Title (de)

ABRICHTEVORRICHTUNG UND ABRICHTUNGSVERFAHREN FÜR SCHLEIFSCHEIBE

Title (fr)

DISPOSITIF ET PROCEDE DE RECTIFICATION DE MEULE

Publication

**EP 1974860 A4 20150902 (EN)**

Application

**EP 06843748 A 20061227**

Priority

- JP 2006326378 W 20061227
- JP 2005376981 A 20051228
- JP 2006336595 A 20061214

Abstract (en)

[origin: EP1974860A1] A truing apparatus for a grinding wheel is provided with a correcting tool which is held so as to rotate, and the grinding wheel which is rotating is corrected by the correcting tool. The correcting tool includes a peripheral surface truer having a truer surface formed on its rotating peripheral surface, and an end surface truer having a truer surface formed on its end surface in a direction of a rotation axis thereof. The rotation axis of the correcting tool is arranged substantially perpendicularly to a rotation axis of the grinding wheel so that an end surface of the grinding wheel may be corrected with the peripheral surface truer, and a peripheral surface of the grinding wheel may be corrected with the end surface truer.

IPC 8 full level

**B24B 53/053** (2006.01); **B24B 53/00** (2006.01); **B24B 53/02** (2012.01); **B24B 53/047** (2006.01)

CPC (source: EP US)

**B24B 53/053** (2013.01 - EP US); **B24B 53/14** (2013.01 - EP US)

Citation (search report)

- [X] GB 991857 A 19650512 - FRANCO FENOCCHIO, et al
- [I] WO 8805367 A1 19880728 - TSCHUDIN WERKZEUGMASCH [CH]
- See references of WO 2007077964A1

Cited by

CN103894930A; DE102009041381A1; US2012058716A1; US9108294B2

Designated contracting state (EPC)

DE

DOCDB simple family (publication)

**EP 1974860 A1 20081001**; **EP 1974860 A4 20150902**; JP 2007196367 A 20070809; JP 5018058 B2 20120905; US 2009280726 A1 20091112; WO 2007077964 A1 20070712

DOCDB simple family (application)

**EP 06843748 A 20061227**; JP 2006326378 W 20061227; JP 2006336595 A 20061214; US 15953406 A 20061227