

Title (en)  
METHOD AND ARRANGEMENTS FOR ENCODING AUDIO SIGNALS

Title (de)  
VERFAHREN UND ANORDNUNGEN ZUR AUDIOSIGNALKODIERUNG

Title (fr)  
PROCÉDÉ ET DISPOSITIFS POUR CODER UN SIGNAL AUDIO

Publication  
**EP 1979899 A1 20081015 (DE)**

Application  
**EP 06706507 A 20060131**

Priority  
EP 2006000811 W 20060131

Abstract (en)  
[origin: WO2007087823A1] According to the invention, an excitation signal (EXC) is generated as a result of sampled excitation values in order to excite an audio synthesis filter (ASYN), the generated sampled excitation values being continuously stored in an adaptive codebook (ACB). A noise generator (NOISE) is provided which continuously generates random sampled values. A sequence (EXC\_P) of the stored sampled excitation values is selected from the adaptive codebook (ACB) based on a fed audio fundamental frequency parameter (PITCH) by means of which a time gap between the sequence (EXC\_P) that is to be selected and the actual time reference is predefined. The excitation signal (EXC) is generated by mixing the selected sequence (EXC\_P) with a random sequence (EXC\_N) encompassing actual random sampled values of the noise generator.

IPC 8 full level  
**G10L 19/12** (2006.01); **G10L 21/02** (2006.01); **G10L 21/038** (2013.01); **G10L 19/00** (2006.01)

CPC (source: EP US)  
**G10L 19/12** (2013.01 - EP US); **G10L 21/038** (2013.01 - EP US); **G10L 2019/0001** (2013.01 - EP)

Citation (search report)  
See references of WO 2007087823A1

Designated contracting state (EPC)  
DE FR GB IT SE

DOCDB simple family (publication)  
**WO 2007087823 A1 20070809**; CN 101336449 A 20081231; CN 101336449 B 20111019; EP 1979899 A1 20081015; EP 1979899 B1 20150311; US 2009012782 A1 20090108; US 8135584 B2 20120313

DOCDB simple family (application)  
**EP 2006000811 W 20060131**; CN 200680052140 A 20060131; EP 06706507 A 20060131; US 22335906 A 20060131