

Title (en)
Facade construction with reduced linear heat flow coefficients

Title (de)
Fassadenkonstruktion mit verringertem linearen Wärmedurchgangskoeffizienten

Title (fr)
Construction de façade dotée d'un coefficient de passage de chaleur linéaire réduit

Publication
EP 1983123 B1 20160727 (DE)

Application
EP 08154687 A 20080417

Priority
DE 102007018305 A 20070418

Abstract (en)
[origin: EP1983123A2] The construction has a basic profile (12) made of metal, and integrally formed with or fixed on a base frame profile (10), which is made of wood or metal. Infill elements (20, 40) rest against inner sealing strips (18), which are attached at the basic profile. The strips have a breadth of 5 millimeters and a height of 3 millimeters, and the infill elements have a laminated insulation glass comprising a spacer with warm edges. The elements have a total thickness of 24 nanometers, where linear heat transmission coefficient of the elements does not exceed a specific value.

IPC 8 full level
E04B 2/96 (2006.01); **E06B 3/62** (2006.01)

CPC (source: EP)
E04B 2/967 (2013.01)

Citation (opposition)
Opponent : Raico Bautechnik GmbH

- DE 202005000603 U1 20060524 - SCHUECO INT KG [DE]
- DE 29918219 U1 200000817 - RAICO BAUTECHNIK GMBH [DE]
- DE 20304039 U1 20030717 - SCHULZ HARALD [DE]
- DE 3633620 A1 19880414 - GARTNER & CO J [DE]
- WO 03023157 A1 20030320 - FELDMEIER FRANZ [DE]
- DE 102006061360 A1 20080626 - FUTECH GMBH [DE]
- "RAICOTHERM Das Multisystem für Stahl-, Holz- und Aluminiumfassaden", KATALOG DER FA. RAICO, November 2000 (2000-11-01), XP055377185
- "THERM+ Holzfassaden, Holzwintergärten, Holzglasdächer", KATALOG DER FA. RAICO, September 2005 (2005-09-01), XP055377190
- "Anhang A (informativ) - Wärmeleitfähigkeit ([lambda]-Wert) ausgewählter Werkstoffe in Tabellenform", EN ISO 10077-2:2003 (D), 2003, XP055377199
- "Thermix Abstandshalter für Isolierglas", PRODUKTBLATT DER FA. ENSINGER, April 2004 (2004-04-01), XP055377204
- "Wärmetechnisches Verhalten von Vorhangsfassaden - Berechnung des Wärmedurchgangskoeffizienten", ENTWURF ZUR DIN EN 13947, June 2006 (2006-06-01), XP055377212
- "Wärmedurchgangskoeffizienten Uf und Linearer Wärmedurchgangskoeffizient Psi", DATENBLATT RAICO, 12 April 2017 (2017-04-12), XP055377218
- "THERM+ 76 H-I Isobloc P", ZERTIFIKAT PFOSTEN-RIEGEL-FASSADE IN HOLZ-ALUMINIUM-BAUWEISE, 2004, XP055377224
- "eböks Elchtest für den Glasrandverbund: Thermix-Abstandhalter", GFF - ZEITSCHRIFT FÜR GLAS FENSTER FASSADE, August 1998 (1998-08-01), pages 457 - 459, XP055377228

Cited by
CN104314206A

Designated contracting state (EPC)
AT CH DE IT LI

DOCDB simple family (publication)
EP 1983123 A2 20081022; EP 1983123 A3 20110518; EP 1983123 B1 20160727; DE 102007018305 A1 20081023

DOCDB simple family (application)
EP 08154687 A 20080417; DE 102007018305 A 20070418