

Title (en)  
CONTACT DEVICE

Title (de)  
KONTAKTVORRICHTUNG

Title (fr)  
DISPOSITIF DE CONTACT

Publication  
**EP 1984984 A1 20081029 (DE)**

Application  
**EP 07703262 A 20070205**

Priority  
• EP 2007000952 W 20070205  
• DE 102006005940 A 20060209

Abstract (en)  
[origin: WO2007090590A1] The invention relates to a contact device (10) having at least a first contact region (12) which is designed for electrical connection to an electric line (102), and having at least a second contact region (14) which is designed for electrical connection to a flexible printed circuit board (104) or some other contact medium which experiences damage from repeated soldering, in which the first contact region (12) and the second contact region (14) are electrically connected. The invention provides here that between the first contact region (12) and the second contact region (14) a third region (16) is provided which has a lower thermal conductivity per unit length than the thermal conductivity per unit length of the first contact region (12) and/or which is the thermal conductivity per unit length of the second contact region (14).

IPC 8 full level  
**H01R 12/38** (2006.01)

CPC (source: EP US)  
**H01R 4/023** (2013.01 - EP US); **H01R 11/01** (2013.01 - EP US); **H01R 11/03** (2013.01 - EP US); **H01R 12/592** (2013.01 - EP US); **H01R 12/63** (2013.01 - EP US); **Y10T 29/49149** (2015.01 - EP US)

Citation (search report)  
See references of WO 2007090590A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**WO 2007090590 A1 20070816**; AT E437455 T1 20090815; DE 102006005940 B3 20070927; DE 502007001125 D1 20090903; EP 1984984 A1 20081029; EP 1984984 B1 20090722; US 2009029573 A1 20090129; US 7666003 B2 20100223

DOCDB simple family (application)  
**EP 2007000952 W 20070205**; AT 07703262 T 20070205; DE 102006005940 A 20060209; DE 502007001125 T 20070205; EP 07703262 A 20070205; US 18858808 A 20080808