

Title (en)

METHOD FOR PRODUCING A NOISE INSULATION PIECE

Title (de)

VERFAHREN ZUM HERSTELLEN EINES SCHALLISOLATIONSTEIL

Title (fr)

PROCÉDÉ DE FABRICATION D'UN ÉLÉMENT D'INSONORISATION

Publication

EP 1986888 A1 20081105 (DE)

Application

EP 07703506 A 20070216

Priority

- EP 2007001375 W 20070216
- DE 102006007784 A 20060220

Abstract (en)

[origin: DE102006007784A1] In a process to manufacture automotive floorpan sound insulation with or without a carpet (1), a base-mass floor covering layer (1) is placed on top of a layer of deep drawn thermoplastic granules (3). Following the deep drawing process, the combined (4) weight of floor covering and granules reaches a pre-determined mass value. Prior to the deep drawing process, the granules are heated to effect a bond with the base-mass layer. The granules and base-mass materials are both thermoplastics with about the same melting point. The granules have spring-like characteristics. The density of the granular layer varies locally in accordance with the sound muffling characteristics required. The granules and base-mass are joined by sintering.

IPC 8 full level

B60R 13/08 (2006.01)

CPC (source: EP US)

B29C 44/146 (2013.01 - EP US); **B29C 44/445** (2013.01 - EP US); **B60R 13/083** (2013.01 - EP US); **B29L 2031/3017** (2013.01 - EP US);
Y10T 428/249953 (2015.04 - EP US); **Y10T 428/31551** (2015.04 - EP US); **Y10T 442/699** (2015.04 - EP US)

Citation (search report)

See references of WO 2007096100A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

DE 102006007784 A1 20070823; EP 1986888 A1 20081105; JP 2009527378 A 20090730; US 2009088039 A1 20090402;
WO 2007096100 A1 20070830

DOCDB simple family (application)

DE 102006007784 A 20060220; EP 07703506 A 20070216; EP 2007001375 W 20070216; JP 2008555678 A 20070216;
US 28012807 A 20070216