

Title (en)
Detent fitting

Title (de)
Rastbeschlag

Title (fr)
Ferrure à cran d'arrêt

Publication
EP 1989960 B1 20101117 (DE)

Application
EP 08101337 A 20080206

Priority
DE 202007006758 U 20070508

Abstract (en)
[origin: EP1989960A1] The fitting has a detent lever (1) designed as a circular arc shaped head (3) with external teeth (4) at an end, where the teeth correspond to teeth (7) of a spring-loaded blocking unit (6). The blocking unit is pivotably fastened at a strap (2) by a common pivoting axis (5) arranged centrally in the head, and is designed as a wedge-shaped blocking unit. The blocking unit movably rests against a stop edge (9) of the strap with its side turned away from the teeth of the blocking unit.

IPC 8 full level
A47C 1/025 (2006.01); **A47C 1/026** (2006.01); **A47C 20/04** (2006.01)

CPC (source: EP)
A47C 1/026 (2013.01); **A47C 7/38** (2013.01); **A47C 7/402** (2013.01)

Cited by
DE102011116943A1; DE102011017301A1; DE102017129057A1; DE202012000285U1; DE102011116943B4; DE102011017301B4;
EP3569107A1; DE202017107438U1

Designated contracting state (EPC)
AT DE GB IT PL

DOCDB simple family (publication)
EP 1989960 A1 20081112; **EP 1989960 B1 20101117**; AT E488158 T1 20101215; DE 202007006758 U1 20070719;
DE 502008001798 D1 20101230; PL 1989960 T3 20110630

DOCDB simple family (application)
EP 08101337 A 20080206; AT 08101337 T 20080206; DE 202007006758 U 20070508; DE 502008001798 T 20080206;
PL 08101337 T 20080206