

Title (en)
INSULATING SWITCHING ROD WITH A CONTACT PRESSURE ARRANGEMENT COMPRISING A PLURALITY OF HELICAL COMPRESSION SPRINGS WOUND IN OPPOSITE SENSES

Title (de)
ISOLIERENDE SCHALTSTANGE MIT EINEN, AUS MEHRERE GEGENLÄUFIG GEWICKELTE SCHRAUBENDRUCKFEDERN BESTEHENDE, KONTAKTDRUCKANORDNUNG

Title (fr)
TRINGLE ISOLANTE DE COMMUTATION DOTÉE D'UN SYSTÈME DE POUSSOIR DE CONTACT CONSTITUÉ DE PLUSIEURS RESSORTS HELICOÏDAUX DE POUSSÉE ENROULÉS DANS DES SENS OPPOSÉS

Publication
EP 1999768 B1 20131030 (DE)

Application
EP 07726925 A 20070315

Priority
• EP 2007052435 W 20070315
• DE 102006015308 A 20060329

Abstract (en)
[origin: WO2007113089A1] With regard to an insulating switching rod for initiating a drive movement into a moving contact of an electrical contact system of a switching device, and for producing a contact force when the contact system is in the closed state, with a clamping apparatus which is arranged in a cavity for a drive element of the switching rod in order to maintain the contact force, which has a greater contact force with a compact design, and ensures constant spring characteristics as well as low wear over the entire useful life, it is proposed that the clamping apparatus comprises a helical compression spring arrangement.

IPC 8 full level
H01H 1/50 (2006.01); **H01H 3/46** (2006.01); **H01H 33/66** (2006.01)

CPC (source: EP US)
H01H 1/50 (2013.01 - EP US); **H01H 33/666** (2013.01 - EP US); **H01H 2033/6667** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
DE 102006015308 A1 20071011; CN 101395684 A 20090325; CN 101395684 B 20101208; EP 1999768 A1 20081210; EP 1999768 B1 20131030; ES 2435514 T3 20131220; RU 2008142737 A 20100510; US 2010078302 A1 20100401; WO 2007113089 A1 20071011

DOCDB simple family (application)
DE 102006015308 A 20060329; CN 200780008032 A 20070315; EP 07726925 A 20070315; EP 2007052435 W 20070315; ES 07726925 T 20070315; RU 2008142737 A 20070315; US 29501507 A 20070315