

Title (en)  
AIR CONDITIONER

Title (de)  
KLIMAANLAGE

Title (fr)  
APPAREIL DE CONDITIONNEMENT D'AIR

Publication  
**EP 2003407 A9 20090506 (EN)**

Application  
**EP 07740810 A 20070402**

Priority  
• JP 2007057374 W 20070402  
• JP 2006105754 A 20060406

Abstract (en)  
[origin: EP2003407A2] [Object of the Invention] An object of the present invention is to provide an air conditioner whose operation mode is switchable between cooling mode and heating mode using highly pressurized hot gas in refrigerant cycle, wherein both a cooling mode operation for variably controlling the displacement of the variable displacement compressor, thereby controlling car interior cooling temperature to a predetermined level, and a heating mode operation for variably controlling the displacement of the variable displacement compressor, thereby controlling car interior heating temperature to a predetermined level, can be implemented. [Disclosure of the Invention] An air conditioner comprises a variable displacement compressor and a controller 400. The variable displacement compressor comprises a control valve provided with a valve body, a pressure sensitive mechanism 300A for sensing the lower pressure side pressure of a refrigerating cycle acting to force the valve body and a solenoid 300B for forcing the valve body based on an input electric current, position of the control valve is controlled to vary internal pressure of a control chamber, thereby variably controlling the displacement of the variable displacement compressor. The controller 400 controls the input electric current to the solenoid 300B to control the position of the control valve. Operation of the air conditioner is switchable between cooling mode and heating mode using highly pressurized hot gas in the refrigerant cycle. During the cooling mode operation, the controller 400 controls the input electric current to the solenoid 300B to operate the control valve based on the lower pressure side pressure of the refrigerant acting on the pressure sensitive mechanism 300A and the quantity of the input electric current to the solenoid 300B, and during the heating mode operation it controls the input electric current to the solenoid 300B to operate the control valve based not on the lower pressure side pressure of the refrigerant cycle acting on the pressure sensitive mechanism 300A but only on the quantity of the input electric current to the solenoid 300B.

IPC 8 full level  
**F25B 1/00** (2006.01); **F04B 27/14** (2006.01); **F04B 49/00** (2006.01); **F24F 11/02** (2006.01); **F25B 1/02** (2006.01)

CPC (source: EP KR US)  
**F04B 27/1804** (2013.01 - EP KR US); **F24F 11/67** (2017.12 - KR); **F24F 11/83** (2017.12 - EP US); **F24F 11/84** (2017.12 - EP KR US); **F24F 11/85** (2017.12 - KR); **F25B 41/20** (2021.01 - EP KR US); **F25B 41/24** (2021.01 - EP US); **F25B 49/022** (2013.01 - EP KR US); **F04B 2027/1827** (2013.01 - EP KR US); **F04B 2027/1854** (2013.01 - EP KR US); **F04B 2027/1859** (2013.01 - EP KR US); **F24F 2140/12** (2017.12 - EP KR US); **F24F 2221/54** (2013.01 - EP KR US); **F25B 2400/0403** (2013.01 - EP KR US); **F25B 2400/0411** (2013.01 - EP KR US); **F25B 2400/076** (2013.01 - EP US); **F25B 2600/0271** (2013.01 - EP KR US); **F25B 2700/1933** (2013.01 - KR); **F25B 2700/21152** (2013.01 - KR)

Citation (search report)  
See references of WO 2007119641A1

Cited by  
DE102012003567A1; WO2013178762A1

Designated contracting state (EPC)  
DE FR HU

DOCDB simple family (publication)  
**EP 2003407 A2 20081217**; **EP 2003407 A4 20090304**; **EP 2003407 A9 20090506**; CN 101416003 A 20090422; CN 101416003 B 20101215; JP 2007278593 A 20071025; JP 4799252 B2 20111026; KR 101012529 B1 20110207; KR 20080104354 A 20081202; US 2009173094 A1 20090709; US 8117858 B2 20120221; WO 2007119641 A1 20071025

DOCDB simple family (application)  
**EP 07740810 A 20070402**; CN 200780012111 A 20070402; JP 2006105754 A 20060406; JP 2007057374 W 20070402; KR 20087023833 A 20070402; US 29608907 A 20070402