

Title (en)

Parting device and removal method of a faulty weft in a weaving loom

Title (de)

Teilungsvorrichtung und Verfahren zur Entfernung eines fehlerhaften Schussfadens in einer Webmaschine

Title (fr)

Dispositif de séparation et procédé de suppression d'une trame défectueuse dans un métier à tisser

Publication

EP 2006430 B1 20101110 (EN)

Application

EP 07425386 A 20070622

Priority

EP 07425386 A 20070622

Abstract (en)

[origin: EP2006430A1] A device and a parting method of a faulty weft in a weaving loom are disclosed, wherein a plurality of tip heads (2) is used, arranged substantially crosswise to the fabric being woven on the loom and aligned to the weft yarns, said tip heads (2) being movable according to the longitudinal axis thereof and simultaneously movable crosswise to the longitudinal axis thereof, so as to wedge in between the last-but-one weft and a last faulty weft and detach the latter before removal of the same.

IPC 8 full level

D03D 51/08 (2006.01)

CPC (source: EP)

D03D 51/085 (2013.01)

Cited by

BE1023294B1

Designated contracting state (EPC)

BE CH DE FR IT LI

DOCDB simple family (publication)

EP 2006430 A1 20081224; EP 2006430 B1 20101110; DE 602007010441 D1 20101223

DOCDB simple family (application)

EP 07425386 A 20070622; DE 602007010441 T 20070622