

Title (en)
Discharge lamp socketed on one side

Title (de)
Einseitig gesockelte Entladungslampe

Title (fr)
Lampe à décharge avec culot unique

Publication
EP 2009668 B1 20100120 (DE)

Application
EP 07111394 A 20070629

Priority
EP 07111394 A 20070629

Abstract (en)
[origin: EP2009668A1] The discharge lamp (10) has a blow pipe (40) and a socket (22) provided for mechanical and electrical connection of the lamp with a lamp holder. The blow pipe has a rolling seal (42) that defines a proximal area (11) of the lamp, where the rolling seal is tuned to the socket along a drawing axis (100). The socket forms a plane (E1) and another plane (E2) that is arranged perpendicular to the drawing axis. Contact pins (50, 51) are respectively arranged on the planes, so that the contact pins are arranged and set with respect to each other.

IPC 8 full level
H01J 5/54 (2006.01); **H01J 61/34** (2006.01); **H01J 61/36** (2006.01)

CPC (source: EP)
H01J 5/54 (2013.01); **H01J 61/34** (2013.01); **H01J 61/368** (2013.01)

Cited by
EP2439765A3; WO2009013699A3

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 2009668 A1 20081231; **EP 2009668 B1 20100120**; AT E456152 T1 20100215; DE 202008001737 U1 20080403;
DE 502007002679 D1 20100311

DOCDB simple family (application)
EP 07111394 A 20070629; AT 07111394 T 20070629; DE 202008001737 U 20080208; DE 502007002679 T 20070629