

Title (en)

Lamp for illumination of a surface of a building

Title (de)

Leuchte zur Ausleuchtung einer Gebäudefläche

Title (fr)

Lampe pour éclairer une surface d'un bâtiment

Publication

EP 2019253 B1 20130605 (DE)

Application

EP 08013156 A 20080722

Priority

DE 102007035396 A 20070726

Abstract (en)

[origin: EP2019253A2] The light (10) has a light source arranged at an interior (19) of a cup-shaped curved reflector (21), where the light source is selected from a group consisting of a HIT-TC-CE-lamp and halogen-lower volt-incandescent lamp such as QT 12-aX or LED. A set of cylindrical segments (14a-14n) is arranged at a reflector inner side (30). The inner side exhibits a surface that is curved to an inner area. The segments are arranged between a vertex (S) and a free edge area (R) of the reflector, and a cylinder axis is aligned under a pointed angle along a longitudinal center axis of the reflector.

IPC 8 full level

F21S 8/02 (2006.01); **F21V 7/00** (2006.01); **F21V 7/04** (2006.01); **F21V 7/09** (2006.01); **F21V 7/22** (2006.01); **F21Y 101/00** (2016.01)

CPC (source: EP KR)

F21S 8/02 (2013.01 - EP); **F21V 7/00** (2013.01 - KR); **F21V 7/04** (2013.01 - EP); **F21V 7/048** (2013.01 - EP); **F21V 7/06** (2013.01 - EP); **F21V 7/09** (2013.01 - EP); **F21V 7/24** (2018.01 - EP); **F21W 2131/107** (2013.01 - EP); **F21W 2131/304** (2013.01 - EP)

Cited by

EP3086026A1; EP2216588A1; US11378255B2; WO2020048759A1; WO2016170234A1

Designated contracting state (EPC)

DE ES FR GB IT SE

DOCDB simple family (publication)

EP 2019253 A2 20090128; **EP 2019253 A3 20121121**; **EP 2019253 B1 20130605**; AU 2008203047 A1 20090212; CN 101373050 A 20090225; DE 102007035396 A1 20090129; DE 102007035396 B4 20110414; KR 20090012102 A 20090202; SG 149768 A1 20090227

DOCDB simple family (application)

EP 08013156 A 20080722; AU 2008203047 A 20080710; CN 200810171423 A 20080725; DE 102007035396 A 20070726; KR 20080071479 A 20080723; SG 2008052714 A 20080714