

Title (en)

METHOD OF PRODUCING PNEUMATIC TIRE

Title (de)

VERFAHREN ZUR HERSTELLUNG EINES LUFTREIFENS

Title (fr)

PROCÉDÉ DE PRODUCTION D'UN BANDAGE PNEUMATIQUE

Publication

EP 2025500 A1 20090218 (EN)

Application

EP 07743834 A 20070522

Priority

- JP 2007060400 W 20070522
- JP 2006146631 A 20060526

Abstract (en)

Provided is a method of producing a pneumatic tire, which prevents occurrence of blisters caused by trapped air when a thermoplastic resin film is used as an air permeation prevention layer, and particularly, a method suitable for producing a heavy-duty pneumatic tire. The method of producing a pneumatic tire includes: wrapping a thermoplastic resin film 6 around a making drum 20; winding an unvulcanized tie-rubber sheet 7 on the thermoplastic resin film 6; splicing a winding start portion and a winding end portion of the tie-rubber sheet with each other; and thereafter winding a carcass layer on the tie-rubber sheet 7. In the method, a splice of the tie-rubber sheet is made to be a butt-splice, and an unvulcanized auxiliary rubber sheet 9 is interposed between the tie-rubber sheet 7 and the thermoplastic resin film 6, along a joint 7c of the butt-splice.

IPC 8 full level

B29D 30/30 (2006.01)

CPC (source: EP US)

B29D 30/0681 (2013.01 - EP US); **B29D 30/20** (2013.01 - EP US); **B29D 2030/0682** (2013.01 - EP US); **B29K 2101/12** (2013.01 - EP US); **B29L 2030/008** (2013.01 - EP US)

Cited by

FR2997893A1; WO2014075985A1

Designated contracting state (EPC)

DE FR IT

Designated extension state (EPC)

AL BA HR MK RS

DOCDB simple family (publication)

EP 2025500 A1 20090218; **EP 2025500 A4 20100721**; **EP 2025500 B1 20120808**; CN 101454146 A 20090610; CN 101454146 B 20120718; JP 2007313776 A 20071206; JP 4725416 B2 20110713; US 2009183820 A1 20090723; WO 2007138918 A1 20071206

DOCDB simple family (application)

EP 07743834 A 20070522; CN 200780019306 A 20070522; JP 2006146631 A 20060526; JP 2007060400 W 20070522; US 30099207 A 20070522