

Title (en)

METHOD OF PRODUCING A ROD IN THE TOBACCO-PROCESSING INDUSTRY, AND ROD-MAKING MACHINE

Title (de)

VERFAHREN ZUM HERSTELLEN EINES STRANGS DER TABAK VERARBEITENDEN INDUSTRIE SOWIE STRANGMASCHINE

Title (fr)

PROCÉDÉ DE FABRICATION D'UN BOUDIN DANS L'INDUSTRIE DU TABAC AINSI QUE MACHINE DE FABRICATION DE BOUDINS

Publication

EP 2026670 A1 20090225 (DE)

Application

EP 07725902 A 20070607

Priority

- EP 2007005056 W 20070607
- DE 102006027598 A 20060613

Abstract (en)

[origin: WO2007144110A1] The invention relates to a rod-making machine in the tobacco-processing industry, having a nozzle arrangement (2, 2'), comprising a nozzle opening (10, 10'), having a rod-forming arrangement (6, 6', 12, 12', 13, 13'), comprising a suction-type rod conveyor (6, 6'), the nozzle opening (10, 10') being arranged in the region of the suction-type rod conveyor (6, 6'), and having a trimming arrangement (23), comprising a trimmer (24). The invention also relates to a method of producing a rod (7, 7') in the tobacco-processing industry. The rod-making machine according to the invention is distinguished in that the nozzle opening (10, 10') is arranged upstream of the trimmer (24), as seen in the conveying direction (9, 9') of the suction-type rod conveyor (6, 6'), at a height (h') positioned between the trimmer (24) and the suction-type rod conveyor (6, 6'), or in that the nozzle opening (10, 10') is arranged downstream of the trimmer (24), as seen in the conveying direction (9, 9') of the suction-type rod conveyor (6, 6'), in the region of a suction-type rod conveyor (6, 6'). The method according to the invention is distinguished by the following method steps: conveying separated fibres (17, 17') in the direction of a suction-type rod conveyor (6, 6') in a conveying arrangement (12, 12', 13, 13'), scattering the fibres (17, 17') on a suction-type rod conveyor (6, 6'), feeding an additive (1, 1') to the fibres (17, 17'), trimming to a predeterminable height (h) the fibres (17, 17', 20) scattered on the suction-type rod conveyor (6, 6'), or the fibre cake (20) scattered on the suction-type rod conveyor (6, 6'), wherein the operation of feeding the additive (1, 1') to the fibres (17, 17', 20, 21) takes place just before or just after the trimming operation.

IPC 8 full level

A24C 5/18 (2006.01); **A24D 3/02** (2006.01)

CPC (source: EP)

A24C 5/1892 (2013.01); **A24D 3/0212** (2013.01)

Citation (search report)

See references of WO 2007144110A1

Citation (third parties)

Third party :

EP 0259071 A2 19880309 - PHILIP MORRIS INC [US]

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA HR MK RS

DOCDB simple family (publication)

DE 102006027598 A1 20071227; CN 101466277 A 20090624; EP 2026670 A1 20090225; JP 2009539390 A 20091119; WO 2007144110 A1 20071221

DOCDB simple family (application)

DE 102006027598 A 20060613; CN 200780021858 A 20070607; EP 07725902 A 20070607; EP 2007005056 W 20070607; JP 2009514684 A 20070607