

Title (en)
GENERALIZED HIGH PERFORMANCE NAVIGATION SYSTEM

Title (de)
GENERALISIERTES HOCHLEISTUNGS-NAVIGATIONSSYSTEM

Title (fr)
SYSTÈME DE NAVIGATION À HAUTE PERFORMANCE GÉNÉRALISÉE

Publication
EP 2033010 A2 20090311 (EN)

Application
EP 07873721 A 20070517

Priority

- US 2007011963 W 20070517
- US 80176406 P 20060518
- US 74962707 A 20070516
- US 74965207 A 20070516
- US 74959707 A 20070516
- US 74966707 A 20070516

Abstract (en)
[origin: WO2008105778A2] A generalized high performance navigation system is provided using low earth orbit (LEO) satellites. In one embodiment, a method of performing navigation includes receiving a LEO signal from a LEO satellite, decoding a navigation signal from the LEO signal, receiving first and second ranging signals from first and second ranging sources, respectively, determining calibration information associated with the first and second ranging sources, and calculating a position using the navigation signal, the first and second ranging signals, and the calibration information. In another embodiment, a method of providing a LEO signal from a LEO satellite includes providing a plurality of transmit channels over a plurality of transmit slots, where the transmit channels comprise a set of communication channels and a set of navigation channels, generating a first pseudo random noise (PRN) ranging overlay corresponding to a navigation signal, applying the first PRN ranging overlay to a first set of the navigation channels, and combining the communication channels and the navigation channels into a LEO signal. The method also includes broadcasting the LEO signal from the LEO satellite. A low earth orbit (LEO) satellite data uplink is also provided. A method includes broadcasting the data uplink signal to the LEO satellite. Various approaches to localized jamming of navigation signals are further provided. Modulated noise signals are broadcast over an area of operations to provide a plurality of jamming bursts corresponding to the navigation signal. The jamming bursts are configured to substantially mask the navigation signal in the area of operations.

IPC 8 full level
G01S 5/02 (2006.01); **G01S 5/14** (2006.01); **G01S 19/01** (2010.01); **G01S 19/12** (2010.01); **G01S 19/46** (2010.01)

CPC (source: EP KR)
G01C 21/206 (2013.01 - EP); **G01S 19/01** (2013.01 - EP); **G01S 19/02** (2013.01 - EP); **G01S 19/05** (2013.01 - KR); **G01S 19/08** (2013.01 - KR); **G01S 19/12** (2013.01 - EP); **G01S 19/246** (2013.01 - EP); **G01S 19/31** (2013.01 - KR); **G01S 19/34** (2013.01 - KR); **G01S 19/46** (2013.01 - EP); **H04K 3/224** (2013.01 - EP); **H04K 3/28** (2013.01 - EP); **H04K 3/42** (2013.01 - EP); **H04K 3/43** (2013.01 - EP); **H04K 3/90** (2013.01 - EP)

Citation (search report)
See references of WO 2008105778A2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA HR MK RS

DOCDB simple family (publication)
WO 2008105778 A2 20080904; **WO 2008105778 A3 20090312**; AU 2007347851 A1 20080904; CA 2647582 A1 20080904; CA 2647582 C 20130716; EP 2033010 A2 20090311; EP 2330441 A1 20110608; EP 2330441 B1 20140305; IL 194338 A0 20090803; IL 194338 A 20141231; IL 220751 A0 20120830; JP 2010506138 A 20100225; JP 5253388 B2 20130731; KR 101378272 B1 20140325; KR 20090013760 A 20090205

DOCDB simple family (application)
US 2007011963 W 20070517; AU 2007347851 A 20070517; CA 2647582 A 20070517; EP 07873721 A 20070517; EP 11153732 A 20070517; IL 19433808 A 20080925; IL 22075112 A 20120704; JP 2009511098 A 20070517; KR 20087025734 A 20081021