

Title (en)
Method for preparing a microporous polyethylene film with good property of strength and permeability at high temperature

Title (de)
Verfahren zur Herstellung einer mikroporösen Polyethylenfolie mit guten Festigkeits- und Durchlässigkeitseigenschaften bei hohen Temperaturen

Title (fr)
Méthode de préparation d'un film en polyéthylène microporeux avec de bonnes propriétés de résistance et de perméabilité aux températures élevées

Publication
EP 2036699 A1 20090318 (EN)

Application
EP 08016152 A 20080912

Priority
KR 20070092495 A 20070912

Abstract (en)
The present invention relates to a microporous polyethylene film for use as battery separator. The microporous polyethylene film according to the present invention is characterized by having a film thickness of 5-40 μm , a porosity of 35-55%, a permeability from 2.5×10^{-5} to 10.0×10^{-5} Darcy, a puncture strength of at least 0.10 N/ μm at 90 °C, a puncture angle of at least 30° at 90 °C, and a permeability from 2.0×10^{-5} to 8.0×10^{-5} Darcy after shrinking freely at 120 °C for 1 hour. The microporous polyethylene film in accordance with the present invention has very superior puncture strength and thermal stability at high temperature and takes place of less decrease of permeability due to low thermal shrinkage at high temperature, as well as superior permeability. Therefore, it can be usefully applied in a high-capacity, high-power battery to improve thermal stability and long-term stability of the battery.

IPC 8 full level
B29C 55/14 (2006.01); **B29C 55/16** (2006.01); **C08J 5/18** (2006.01); **H01M 50/417** (2021.01); **H01M 50/491** (2021.01); **B29K 23/00** (2006.01); **B29K 105/00** (2006.01); **B29K 105/04** (2006.01)

CPC (source: EP KR US)
B29C 55/14 (2013.01 - EP KR US); **B29C 55/16** (2013.01 - EP KR US); **C08J 5/18** (2013.01 - EP KR US); **H01M 50/403** (2021.01 - KR); **H01M 50/417** (2021.01 - EP KR US); **H01M 50/489** (2021.01 - KR); **H01M 50/491** (2021.01 - EP KR US); **B29K 2023/065** (2013.01 - EP KR US); **B29K 2105/0073** (2013.01 - EP KR US); **B29K 2105/04** (2013.01 - EP US); **B29K 2105/041** (2013.01 - KR); **C08J 2323/06** (2013.01 - EP KR US); **Y02E 60/10** (2013.01 - EP KR); **Y10T 428/249953** (2015.04 - EP US); **Y10T 428/249978** (2015.04 - EP US)

Citation (applicant)
• US 6949315 B1 20050927 - SAMII GARRIN [US], et al
• US 5641565 A 19970624 - SOGO HIROSHI [JP]
• JP H11322989 A 19991126 - ASAHI CHEMICAL IND
• JP 2003119306 A 20030423 - NITTO DENKO CORP

Citation (search report)
• [X] WO 2006107125 A1 20061012 - SK CORP [KR], et al
• [X] US 2007092705 A1 20070426 - LEE YOUNG-KEUN [KR], et al
• [X] WO 2006123850 A1 20061123 - SK CORP [KR], et al
• [X] EP 1153969 A1 20011114 - TONEN SEKIYUKAGAKU KK [JP]
• [X] US 2006103055 A1 20060518 - HOSHUYAMA IZUMI [JP], et al

Cited by
EP2695223A4; US9159978B2; US11021584B2; US10829600B2; US10586965B2

Designated contracting state (EPC)
DE FR NL

Designated extension state (EPC)
AL BA MK RS

DOCDB simple family (publication)
EP 2036699 A1 20090318; **EP 2036699 A8 20090506**; **EP 2036699 B1 20151223**; CN 101386686 A 20090318; CN 101386686 B 20111109; EP 2777913 A1 20140917; JP 2009070823 A 20090402; JP 5221258 B2 20130626; KR 101288803 B1 20130723; KR 20090027345 A 20090317; US 2009075049 A1 20090319; US 2012156570 A1 20120621; US 8354185 B2 20130115; US 8486521 B2 20130716

DOCDB simple family (application)
EP 08016152 A 20080912; CN 200810211967 A 20080912; EP 14170095 A 20080912; JP 2008234436 A 20080912; KR 20070092495 A 20070912; US 201213403324 A 20120223; US 23211208 A 20080911