

Title (en)
CAM DRIVE

Title (de)
NOCKENTRIEB

Title (fr)
ENTRAÎNEMENT À CAMES

Publication
EP 2041401 A1 20090401 (DE)

Application
EP 07787054 A 20070704

Priority
• EP 2007056752 W 20070704
• DE 102006033403 A 20060719

Abstract (en)
[origin: WO2008009557A1] The present invention relates to a cam drive (1) having a camshaft and having cams (18, 18') arranged thereon and having at least one rocker arm (3) which has a cam follower (2) and which is operatively connected by means of its first arm (4) to a plunger-like bearing (5) and by means of its second arm (6) to at least one gas exchange valve (7) of an associated cylinder. The cam drive (1) also has a device (10) for varying the lift of the at least one gas exchange valve (7). Here, it is essential to the invention that the device (10) is embodied as a clutch device which acts between the plunger-like abutment (5) and the rocker arm (3, 3', 3'') and which has an actuating element (12) which is mounted so as to be rotatable about an axis (13) of the plunger-like abutment (5) at least between two positions, wherein a valve lift in a first, coupled position of the actuating element (12) is varied in comparison with a second, decoupled position.

IPC 8 full level
F01L 1/18 (2006.01); **F01L 1/245** (2006.01); **F01L 13/00** (2006.01)

CPC (source: EP US)
F01L 1/185 (2013.01 - EP US); **F01L 1/2405** (2013.01 - EP US); **F01L 13/0031** (2013.01 - EP US)

Citation (search report)
See references of WO 2008009557A1

Designated contracting state (EPC)
DE FR GB

Designated extension state (EPC)
AL BA HR MK RS

DOCDB simple family (publication)
WO 2008009557 A1 20080124; CN 101495716 A 20090729; DE 102006033403 A1 20080124; EP 2041401 A1 20090401; EP 2041401 B1 20111116; JP 2009543976 A 20091210; US 2010101515 A1 20100429; US 8490587 B2 20130723

DOCDB simple family (application)
EP 2007056752 W 20070704; CN 200780027057 A 20070704; DE 102006033403 A 20060719; EP 07787054 A 20070704; JP 2009519909 A 20070704; US 37337507 A 20070704