

Title (en)

EXTRUSION DIE FOR METALLIC MATERIAL

Title (de)

EXTRUSIONSMATRIZE FÜR EIN METALLISCHES MATERIAL

Title (fr)

FILIÈRE D'EXTRUSION DE MATÉRIAUX MÉTALLIQUES

Publication

EP 2049277 A4 20100317 (EN)

Application

EP 07829274 A 20071001

Priority

- JP 2007069536 W 20071001
- JP 2006271726 A 20061003
- JP 2006275031 A 20061006
- US 88704407 P 20070129
- JP 2007056953 A 20070307
- JP 2007057124 A 20070307

Abstract (en)

[origin: WO2008044620A1] In some preferred embodiments, an extrusion die 10 for a metallic material includes a die case 20 having a pressure receiving portion 21 with a metallic material pressure receiving surface 22 faced rearward against an extrusion direction, a male die 30 disposed in the die case 20, and a female die 40 disposed in the die case 20. The pressure receiving portion 21 is formed into a convex configuration protruded rearward, and a porthole 24 for introducing the metallic material is provided in an outer periphery of the pressure receiving portion 21. A ratio of a flat state opening area Sb of a porthole inlet portion 24e to a flat state area Sa of the pressure receiving portion 21 is set to 0.15 to 0.80. The extrusion die is configured such that the metallic material pressurized against the metallic material pressure receiving surface 22 is introduced into the die case 20 via the porthole 24 and passes through the extrusion hole 11.

IPC 8 full level

B21C 25/00 (2006.01)

CPC (source: EP US)

B21C 23/10 (2013.01 - EP US); **B21C 25/00** (2013.01 - EP US)

Citation (search report)

- [E] EP 1924370 A1 20080528 - SHOWA DENKO KK [JP]
- [X] US 3748885 A 19730731 - CREUZET R
- [X] DE 99405 C
- See references of WO 2008044620A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

WO 2008044620 A1 20080417; EP 2049277 A1 20090422; EP 2049277 A4 20100317; US 2010095731 A1 20100422

DOCDB simple family (application)

JP 2007069536 W 20071001; EP 07829274 A 20071001; US 44370007 A 20071001