

Title (en)
FORM CYLINDER OF A PRINTING MACHINE, COMPRISING A PLURALITY OF SECTIONS IN SERIES IN THE AXIAL DIRECTION ON THE ENVELOPE SURFACE THEREOF, AND PRINTING GROUP COMPRISING SAID FORM CYLINDER

Title (de)
FORMZYLINDER EINER DRUCKMASCHINE MIT MEHREREN IN SEINER AXIALRICHTUNG AUF EINANDER FOLGENDEN ABSCHNITTEN AN SEINER MANTELFLÄCHE SOWIE DRUCKWERK MIT DIESEM FORMZYLINDER

Title (fr)
CYLINDRE PORTE-CLICHÉ D'IMPRIMANTE COMPRENANT PLUSIEURS SECTIONS QUI SE SUIVENT DANS SA DIRECTION AXIALE SUR SA SURFACE PÉRIPHÉRIQUE, ET GROUPE D'IMPRESSION COMPRENANT CE CYLINDRE PORTE-CLICHÉ

Publication
EP 2057018 A1 20090513 (DE)

Application
EP 07786867 A 20070627

Priority

- EP 2007056429 W 20070627
- DE 102006041333 A 20060901
- DE 102006061295 A 20061222
- DE 102007010298 A 20070302
- DE 102007014323 A 20070326

Abstract (en)
[origin: WO2008025584A1] The invention relates to a form cylinder (06) of a printing machine, comprising a plurality of sections (A;B;C;D;E;F) in series in the axial direction on the envelope surface thereof. At least one printing block (01) can be arranged in each of said sections. The form cylinder (06) comprises at least one channel (07) extending in the axial direction thereof, said channel having an opening (08) on the envelope surface of the form cylinder. At least one holding device respectively associated with each section (A;-B;C;D;E;F) is arranged in the, or each, channel. Each holding device can be pneumatically actuated in sections, and at least one recess open on the envelope surface of the form cylinder (06) is formed outside the sections. A device for distributing the compressed air supplied to the form cylinder to the respective sections (A; B; C; D; E; F) is provided in the at least one recess. The device distributing the compressed air supplied to the form cylinder to each section is embodied as an arrangement of a plurality of valves (36). At least one control device (18) is provided outside the form cylinder (06) and used to actuate said valves in a non-contact manner. The control device (18) associated with each valve (36) is oriented towards the envelope surface of the form cylinder (06) in a radial line of influence.

IPC 8 full level
B41F 27/12 (2006.01)

CPC (source: EP US)
B41F 27/1212 (2013.01 - EP US)

Citation (search report)
See references of WO 2008025584A1

Cited by
DE102016208943A1; DE102016208943B4

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA HR MK RS

DOCDB simple family (publication)
WO 2008025584 A1 20080306; CN 101484318 A 20090715; CN 101484318 B 20121010; EP 2057018 A1 20090513; EP 2057018 B1 20130508; US 2009320705 A1 20091231; US 8176845 B2 20120515

DOCDB simple family (application)
EP 2007056429 W 20070627; CN 200780008887 A 20070627; EP 07786867 A 20070627; US 31040407 A 20070627