

Title (en)
Fuel injector with optimised shutoff impact

Title (de)
Kraftstoffinjektor mit optimiertem Absteuerstoß

Title (fr)
Injecteur de carburant doté d'un amortisseur de chocs optimisé

Publication
EP 2058507 B1 20111109 (DE)

Application
EP 08105392 A 20080919

Priority
DE 102007052753 A 20071106

Abstract (en)
[origin: EP2058507A1] The valve (12) has a control chamber (54) formed in a valve piece (44) that is accommodated in an injector body (14), and a fuel injector (10) operated by pressure release or pressurization of the control chamber. An armature guide (38) is provided in the valve piece, and has a release opening (62) downstream to a valve seat (42). The release opening is arranged at the periphery of the armature guide in a non-radial position of an injector axis (22). Multiple control openings are formed on the periphery of the armature guide.

IPC 8 full level
F02M 47/02 (2006.01); **F02M 63/00** (2006.01)

CPC (source: EP)
F02M 47/027 (2013.01); **F02M 63/0015** (2013.01); **F02M 2547/003** (2013.01)

Cited by
EP3431747A1; CN113795665A; WO2019154687A1; WO2010000528A1; WO2016134926A1

Designated contracting state (EPC)
DE ES FR GB IT

DOCDB simple family (publication)
EP 2058507 A1 20090513; EP 2058507 B1 20111109; DE 102007052753 A1 20090507

DOCDB simple family (application)
EP 08105392 A 20080919; DE 102007052753 A 20071106