

Title (en)
COOKING APPARATUS

Title (de)
KOCHVORRICHTUNG

Title (fr)
APPAREIL DE CUISSON

Publication
EP 2061996 B1 20180404 (EN)

Application
EP 06823998 A 20061207

Priority
• KR 2006005291 W 20061207
• KR 20060088296 A 20060912

Abstract (en)
[origin: WO2008032902A1] In order to provide a cooking apparatus that is capable of exhausting a flow escaped from a cooking cavity to the outside through a flow with a different flow path, the present invention discloses a cooking apparatus, which comprises: a cooking cavity provided with a first opening and a second opening; a first flow path extended for a flow to enter into the first opening and come out of the second opening; and a second flow path combining with the flow coming out of the second opening and driving the flow to the outside. Through this structure, it is possible to exhaust a flow escaped from the cooking cavity to the outside of the cooking apparatus through a flow with a different flow path.

IPC 8 full level
F24C 15/00 (2006.01); **H05B 6/64** (2006.01)

CPC (source: EP KR)
F24C 7/046 (2013.01 - KR); **F24C 15/006** (2013.01 - EP KR); **F24C 15/02** (2013.01 - KR); **F24C 15/20** (2013.01 - KR);
H05B 6/6414 (2013.01 - KR); **H05B 6/642** (2013.01 - EP KR)

Citation (examination)
• JP H0795472 B2 19951011
• JP H01221881 A 19890905 - MATSUSHITA ELECTRIC IND CO LTD

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 2008032902 A1 20080320; CN 101512234 A 20090819; CN 101512234 B 20110518; EP 2061996 A1 20090527; EP 2061996 A4 20100331;
EP 2061996 B1 20180404; KR 20080024029 A 20080317; MX 2009002678 A 20090324; RU 2009113560 A 20101020;
RU 2415345 C2 20110327

DOCDB simple family (application)
KR 2006005291 W 20061207; CN 200680055820 A 20061207; EP 06823998 A 20061207; KR 20060088296 A 20060912;
MX 2009002678 A 20061207; RU 2009113560 A 20061207