

Title (en)

Catheter with omni-directional optical tip having isolated optical paths

Title (de)

Katheter mit optischer Spitze für alle Richtungen mit isolierten Strahlengängen

Title (fr)

Cathéter avec pointe optique omnidirectionnelle ayant des trajectoires optiques isolées

Publication

EP 2062545 B1 20120201 (EN)

Application

EP 08253725 A 20081114

Priority

US 94188407 A 20071116

Abstract (en)

[origin: EP2062545A2] A catheter enables real-time light measurements, for example, without limitation, diffuse reflectance, fluorescence, etc., from biological materials, such as tissue (including blood), while performing RF ablation. The catheter tip design isolates illumination and collection paths such that light exits the catheter tip and travels through the tissue of interest (e.g., cardiac tissue or blood) before returning to the catheter tip. Such a design advantageously avoids saturation of the optical detector, and ensures diffusion of the illumination light within the medium of interest. The catheter has a catheter body and a tip electrode. The tip electrode has an exterior shell, an inner layer of diffuse material and a hollow cavity, wherein the inner layer is configured to transmit light outside the tip electrode to a tissue via a set of illumination openings in the shell wall and the hollow cavity is configured to receive light from the tissue via a set of collection openings in the shell wall and the inner layer. An inner surface of the inner layer has an opaque coating to isolate light injected into the inner layer from light collected in the hollow cavity. There are a first optical waveguide extending between the catheter body and the tip electrode to inject light into the inner layer and illuminate the tissue, and a second optical waveguide extending between the catheter body and the tip electrode to collect the recaptured light in the hollow cavity.

IPC 8 full level

A61B 5/00 (2006.01); **A61B 18/14** (2006.01); **A61B 17/00** (2006.01)

CPC (source: EP US)

A61B 5/0084 (2013.01 - EP US); **A61B 18/1492** (2013.01 - EP US); **A61B 2018/00815** (2013.01 - EP US); **A61B 2018/00821** (2013.01 - EP US); **A61B 2018/00982** (2013.01 - EP US); **A61B 2034/2051** (2016.02 - EP US); **A61B 2090/3614** (2016.02 - EP US); **A61B 2218/002** (2013.01 - EP US)

Cited by

US10278775B2; EP2470100A4; EP2446810A1; EP3122279A4; AU2019279955B2; DE102009025659A1; EP2889013A1; EP3384867A1; US10201385B2; WO2017037056A1; WO2017016663A1; WO2013166391A1; US10835313B2; US8577447B2; US10568577B2; US8515521B2; US9204928B2; US11628286B2; US8870758B2; US8900228B2; US10022183B2; WO2015114088A1; US9427141B2; US9855410B2; US10194981B2; US10624526B2; US11490956B2

Designated contracting state (EPC)

DE FR GB IT NL

DOCDB simple family (publication)

EP 2062545 A2 20090527; EP 2062545 A3 20090812; EP 2062545 B1 20120201; BR PI0806160 A2 20091117; CA 2643915 A1 20090516; CA 2643915 C 20171212; CN 101617957 A 20100106; CN 101617957 B 20130508; EP 2208475 A1 20100721; EP 2208475 B1 20110928; JP 2009148550 A 20090709; JP 5550826 B2 20140716; MX 2008014731 A 20090522; RU 2008145034 A 20100520; RU 2491014 C2 20130827; US 2009131931 A1 20090521; US 8500730 B2 20130806

DOCDB simple family (application)

EP 08253725 A 20081114; BR PI0806160 A 20081117; CA 2643915 A 20081117; CN 200810189326 A 20081117; EP 10075155 A 20081114; JP 2008291876 A 20081114; MX 2008014731 A 20081118; RU 2008145034 A 20081114; US 94188407 A 20071116