

Title (en)

VARIABLE DISPLACEMENT COMPRESSOR

Title (de)

VERDICHTER MIT VARIABLER VERDRÄNGUNG

Title (fr)

COMPRESSEUR À CYLINDRÉE VARIABLE

Publication

EP 2063121 A1 20090527 (EN)

Application

EP 07806954 A 20070907

Priority

- JP 2007067522 W 20070907
- JP 2006244691 A 20060908

Abstract (en)

A hinge mechanism (40) of a variable capacity compressor (1) includes an arm (41) protruded toward a tilting member (24) from a rotation member (21), an arm (43) protruded toward the rotation member (21) from the tilting member (24) to receive a rotational torque from the arm (41) of the rotation member, a pin (51) fixed to one of the arm (41) of the rotation member and the arm (43) of the tilting member, and an axial-load receiving surface (53a, 53b) formed on the other of the arm (41) of the rotation member and the arm (43) of the tilting member and configured to be in contact with the pin (51) so as to receive an axial load produced between the rotation member (21) and the tilting member (24). A position where the pin (51) and the axial-load receiving surface (53a) contact with each other when the swash plate (24) has a maximum inclination angle is located within a range of 27 to 90 degrees anterior, in the rotational direction, to a position (TDC) corresponding to the top dead center.

IPC 8 full level

F04B 27/08 (2006.01)

CPC (source: EP KR US)

F04B 25/04 (2013.01 - KR); **F04B 27/08** (2013.01 - KR); **F04B 27/1072** (2013.01 - EP US)

Citation (search report)

See references of WO 2008029919A1

Designated contracting state (EPC)

DE FR GB

Designated extension state (EPC)

AL BA HR MK RS

DOCDB simple family (publication)

EP 2063121 A1 20090527; CN 101512151 A 20090819; CN 101512151 B 20110817; JP 2008064057 A 20080321;
KR 20090052867 A 20090526; US 2011041682 A1 20110224; WO 2008029919 A1 20080313

DOCDB simple family (application)

EP 07806954 A 20070907; CN 200780033159 A 20070907; JP 2006244691 A 20060908; JP 2007067522 W 20070907;
KR 20097005025 A 20090311; US 44035307 A 20070907