

Title (en)

Shielded connection of two terminals by contact between flat interfaces

Title (de)

Abgeschirmte Verbindung von zwei Klemmen durch Kontakt zwischen zwei ebenen Schnittstellen

Title (fr)

Connexion blindée de deux bornes par contact entre interfaces planes

Publication

EP 2063494 B1 20101124 (FR)

Application

EP 08354076 A 20081021

Priority

FR 0708127 A 20071120

Abstract (en)

[origin: EP2063494A1] The device (10) has a deformable insulating support (16) provided with a periphery and two plane end faces (18, 18') that are superimposed at linking surfaces (38, 38') of shielded terminals (30, 30') when the support is deformed by compression between the faces. A conductive electrostatic shielding coating e.g. paint, is provided on the periphery of the support. A cylindrical conductive rod (12) is integrated in the support and opened on the faces at the level of connection pads (14, 14'), where the pads are inscribed in connection surfaces (34, 34') of the terminals. The coating is constituted by over-molding of an insulating elastomer same as that of the support. The support is also made of compressible insulating foam. Independent claims are also included for the following: (1) a connector comprising two terminals (2) a method for electrically connecting two terminals.

IPC 8 full level

H01R 13/22 (2006.01)

CPC (source: EP)

H01R 13/22 (2013.01); **H01R 13/58** (2013.01); **H01R 13/6485** (2013.01); **H01R 13/6599** (2013.01)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 2063494 A1 20090527; EP 2063494 B1 20101124; AT E489744 T1 20101215; CN 101442163 A 20090527; CN 101442163 B 20131106; DE 602008003648 D1 20110105; FR 2923954 A1 20090522; FR 2923954 B1 20100226

DOCDB simple family (application)

EP 08354076 A 20081021; AT 08354076 T 20081021; CN 200810181272 A 20081118; DE 602008003648 T 20081021; FR 0708127 A 20071120