

Title (en)
DC/DC POWER CONVERTING APPARATUS

Title (de)
GLEICHSTROM-GLEICHSTROM-WANDLERVORRICHTUNG

Title (fr)
APPAREIL CONVERTISSEUR DE COURANT CC/CC

Publication
EP 2063520 A1 20090527 (EN)

Application
EP 07737244 A 20070531

Priority

- JP 2007000588 W 20070531
- JP 2006250443 A 20060915

Abstract (en)
Three or more circuits (A1-A4), in which series-connected low-voltage and high-voltage side switches made of MOSFETs having parasitic diodes are connected across positive and negative terminals of each of smoothing capacitors (Cs1-Cs4), are connected in series. One of elementary series circuits, each including a capacitor (Cr) and an inductor (Lr), is disposed between any adjacent two of the circuits with the elementary series circuits set to have the same period of resonance. The MOSFETs of rectifier circuits (A2-A4) are brought into an ON state simultaneously with the MOSFETs of a driving inverter circuit (A1) and brought into an OFF state earlier than the MOSFETs of the driving inverter circuit (A1) by a period of time not exceeding a time period (t) equal to (period of resonance)/2. With this arrangement, a resonance phenomenon of the capacitor (Cr) and the inductor (Lr) is used and conduction loss in the rectifier circuits (A2-A4) is reduced in DC/DC power conversion performed through charging and discharging operation of the capacitor (Cr).

IPC 8 full level
H02M 3/07 (2006.01); **H02M 3/158** (2006.01); **H02M 7/48** (2007.01)

CPC (source: EP US)
H02J 7/0016 (2013.01 - EP US); **H02M 3/158** (2013.01 - EP US); **H02M 1/0077** (2021.05 - EP US)

Cited by
EP2863529A1; EP2719062B1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 2063520 A1 20090527; EP 2063520 A4 20121107; CN 101517876 A 20090826; CN 101517876 B 20120215; JP 4819902 B2 20111124; JP WO2008032425 A1 20100121; US 2009261793 A1 20091022; US 8040702 B2 20111018; WO 2008032425 A1 20080320

DOCDB simple family (application)
EP 07737244 A 20070531; CN 200780033805 A 20070531; JP 2007000588 W 20070531; JP 2008534233 A 20070531; US 43982907 A 20070531