

Title (en)

Method of operating a sheet printing press with lacquering unit

Title (de)

Verfahren zum Betreiben einer Bogendruckmaschine mit Lackwerk

Title (fr)

Procédé pour faire fonctionner une presse d'impression de feuilles avec groupe de vernissage

Publication

**EP 2067621 B1 20101027 (DE)**

Application

**EP 08019877 A 20081114**

Priority

DE 102007058284 A 20071204

Abstract (en)

[origin: EP2067621A1] The method involves accomplishing a paint form change at a plate cylinder (22) of a painting unit (14) parallel to an assembling function at a printing unit (13) such that the painting unit is completely decoupled from a main drive of a sheet fed printing machine (10) to the paint change form. The cylinder of the painting unit is driven by a separate drive. The printing unit is synchronously coupled to the main drive of the machine after implementing the paint form change. Cylinders of the printing unit are driven by the main drive.

IPC 8 full level

**B41F 23/08** (2006.01); **B41F 13/008** (2006.01)

CPC (source: EP)

**B41F 13/008** (2013.01); **B41F 23/08** (2013.01)

Cited by

CN102811862A; US8850983B2; DE102015118741A1; WO2011069861A1; WO2012123097A1; US9365030B2; DE102013012708B4

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 2067621 A1 20090610**; **EP 2067621 B1 20101027**; AT E485944 T1 20101115; DE 102007058284 A1 20090610; DE 502008001633 D1 20101209; JP 2009137298 A 20090625

DOCDB simple family (application)

**EP 08019877 A 20081114**; AT 08019877 T 20081114; DE 102007058284 A 20071204; DE 502008001633 T 20081114; JP 2008308716 A 20081203