

Title (en)

Method for mounting a rubber blanket in offset printing

Title (de)

Verfahren zur Montage eines Gummituchs im Offset-Druck

Title (fr)

Procédé de montage d'un blanchet de caoutchouc en impression offset

Publication

EP 2070716 B1 20130821 (DE)

Application

EP 07122754 A 20071210

Priority

EP 07122754 A 20071210

Abstract (en)

[origin: EP2070716A1] The pad has a flexible layer (1) exhibiting a modulus of elasticity in a range of 1 mega Pascal to 1000 mega Pascal, where the modulus of elasticity is measured in accordance with DIN International Organization for Standardization (ISO) 527-1, and no inelastic layer is provided in the pad. The flexible layer contains polyurethane, PVC, silicone, silicone gel, nitrile-butyl-rubber, ethylene-propylene-rubber, polyethylene, and polypropylene. A multi-layered pressure sensible adhesive glue (2) fastens the pad to a rubber blanket cylinder. An independent claim is also included for a method for assembling a rubber blanket in an offset printing.

IPC 8 full level

B41N 10/02 (2006.01); **B41N 10/04** (2006.01)

CPC (source: EP)

B41N 6/00 (2013.01); **B41N 10/02** (2013.01); **B41N 10/04** (2013.01); **B41N 2210/06** (2013.01); **B41N 2210/14** (2013.01)

Citation (examination)

- US 5476712 A 19951219 - HARTMAN WILLIAM G [US], et al
- EP 0845515 A2 19980603 - BEIERSDORF AG [DE]

Cited by

WO2023084547A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 2070716 A1 20090617; EP 2070716 B1 20130821

DOCDB simple family (application)

EP 07122754 A 20071210