

Title (en)
Lock

Title (de)
Schloss

Title (fr)
Serrure

Publication
EP 2072726 A3 20130501 (DE)

Application
EP 08019389 A 20081105

Priority
DE 202007017644 U 20071218

Abstract (en)

[origin: EP2072726A2] The lock has lock bolts (6,9) and a manually operated actuating element, where the lock bolts and the actuating element both stand in operative connection with each other. The lock bolts are moved backwardly from an extended position in a withdrawn position by the actuation of the actuating element. A blocking element is provided, by which the withdrawing of the lock bolt is inhibited. The operative connection between the actuating element and the lock bolt is weakened or disconnected in the interlocked condition of the lock bolt.

IPC 8 full level
E05B 55/00 (2006.01); **E05C 9/18** (2006.01)

CPC (source: EP)
E05B 55/06 (2013.01); **E05C 9/1841** (2013.01)

Citation (search report)

- [XI] CH 316665 A 19561031 - JENSEN HERMANN BORGE FUNCK [DK]
- [XI] EP 0653535 A1 19950517 - SCHLOSS UND BESCHLAEgefABRIK A [CH]
- [XI] DE 46087 C
- [A] EP 1087084 A2 20010328 - FLIETHER KARL GMBH & CO [DE]

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA MK RS

DOCDB simple family (publication)

DE 202007017644 U1 20090430; EP 2072726 A2 20090624; EP 2072726 A3 20130501; EP 2072726 B1 20150826; HU E025627 T2 20160329;
PL 2072726 T3 20160229; SI 2072726 T1 20151231

DOCDB simple family (application)

DE 202007017644 U 20071218; EP 08019389 A 20081105; HU E08019389 A 20081105; PL 08019389 T 20081105; SI 200831530 T 20081105