

Title (en)
Coolant pump

Title (de)
Kühlmittelpumpe

Title (fr)
Pompe à réfrigérant

Publication
EP 2072825 A3 20120328 (DE)

Application
EP 08172030 A 20081217

Priority
DE 102007055907 A 20071221

Abstract (en)

[origin: EP2072825A2] The pump has a rotor (7) and a stator (8) are cylindrically formed and concentrically arranged together under retention of an axially running air gap (12) through which coolant flows, where the rotor is designed as an external rotor. A pump wheel (1) is axially fastened to the rotor by adjusting a rotational axis (16) of the rotor, and the rotor is extended into a rotor casing (13). The casing is attached to a pump chamber (3), and the stator is arranged in a stator casing (14). The stator casing is concentrically provided within the rotor casing, and is sealed against the rotor casing.

IPC 8 full level
F04D 13/06 (2006.01); **F04D 15/02** (2006.01); **F04D 29/047** (2006.01)

CPC (source: EP)
F04D 13/0673 (2013.01); **F04D 15/0254** (2013.01); **F04D 29/0473** (2013.01)

Citation (search report)

- [XI] US 2007020129 A1 20070125 - HUANG CHING-HSING [CN], et al
- [XI] US 2004234395 A1 20041125 - HATANO MAKOTO [JP]
- [XI] DE 202005019163 U1 20060427 - SUPER ELECTRONICS CO [TW]
- [XI] US 2007177993 A1 20070802 - NAKAMICHI KAZUTAKA [JP], et al
- [XI] US 2006045734 A1 20060302 - HONG ALEX [TW], et al
- [XI] US 2006083643 A1 20060420 - CHEN HOU-CHU [TW], et al
- [XI] US 2007274828 A1 20071129 - FUKUKI HARUMI [JP]
- [XI] US 2001033800 A1 20011025 - DEAI JUNJI [JP], et al

Cited by

EP3379085A1; GB2567582A; GB2567581A; GB2567582B; GB2567581B; WO2011035971A3; WO2018029116A1; WO2018029115A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

EP 2072825 A2 20090624; EP 2072825 A3 20120328; DE 102007055907 A1 20090625

DOCDB simple family (application)

EP 08172030 A 20081217; DE 102007055907 A 20071221