Title (en)

Pyrotechnical cutter fuse and method of manufacturing such a fuse

Title (de)

Pyrotechnische Schneidschnur und Herstellungsverfahren einer solchen Schnur

Title (fr)

Cordeau de découpe pyrotechnique et procédé de fabrication d'un tel cordeau

Publication

EP 2075525 B1 20110907 (FR)

Application EP 08

EP 08291238 A 20081224

Priority

FR 0709085 A 20071226

Abstract (en)

[origin: EP2075525A1] The pyrotechnic cutting cord (1) useful in military aircrafts and launchers, comprises an explosive material (5) disposed in a casing (2), and a metallic profile that forms a coating of the cut and is applied against the explosive material. The casing comprises two distinct parts assembled one after the other. The two distinct parts include a thin rear part or a covering (2a), and a thick front part (2b). The front part comprises two lateral wings (3a, 3b) forming a support for the covering and connected by a median zone that forms the coating of the cut. The pyrotechnic cutting cord (1) useful in military aircrafts and launchers, comprises an explosive material (5) disposed in a casing (2), and a metallic profile that forms a coating of the cut and is applied against the explosive material (5) disposed in a casing (2), and a metallic profile that forms a coating of the cut and is applied against the explosive material. The casing comprises two distinct parts assembled one after the other. The two distinct parts include a thin rear part or a covering (2a), and a thick front part (2b). The front part comprises two lateral wings (3a, 3b) forming a support for the covering (2a), and a thick front part (2b). The front parts assembled one after the other. The two distinct parts include a thin rear part or a covering (2a), and a thick front part (2b). The front part comprises two lateral wings (3a, 3b) forming a support for the covering and connected by a median zone that forms the coating of the cut, and is constituted by the metallic profile. The covering has a constant thickness, and is made of plastic or a composite material. The explosive material is applied in the form of a narrow sheet on the median zone of the front part. The narrow sheet is maintained in a place by the covering. An independent claim is included for a process for the fabrication of a cutting cord.

IPC 8 full level

F42B 1/028 (2006.01); C06C 5/04 (2006.01); F42B 1/036 (2006.01)

CPC (source: EP)

C06C 5/04 (2013.01); F42B 1/028 (2013.01); F42B 1/036 (2013.01)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 2075525 A1 20090701; EP 2075525 B1 20110907; AT E523755 T1 20110915; ES 2372993 T3 20120130; FR 2925955 A1 20090703

DOCDB simple family (application)

EP 08291238 A 20081224; AT 08291238 T 20081224; ES 08291238 T 20081224; FR 0709085 A 20071226