

Title (en)

Device for adjusting the centre distance between the binding means of a ski binding

Title (de)

Vorrichtung zur Einstellung des Mittenabstands zwischen den Bindungselementen einer Skibindung

Title (fr)

Dispositif de réglage de la distance entre le centre de moyens de fixation de fixations de ski

Publication

EP 2082789 A1 20090729 (EN)

Application

EP 09150349 A 20090109

Priority

IT PN20080001 A 20080125

Abstract (en)

The present invention refers to a device for adjusting the centre distance between the binding means of a ski binding, comprising: a first and a second carriage (3, 4) slidably associable to a plate (2, 2a, 2b) which is in turn associable to a ski and extends along a longitudinal axis essentially parallel to the longitudinal extension of the ski; the first and the second carriages (3, 4) are adapted to support respective binding means for a ski boot. The device further comprises linking means for mutually linking the first and the second carriages (3, 4) and capable to cause a simultaneous and synchronous sliding motion of the first and second carriages (3, 4) along the longitudinal axis of the plate (2, 2a, 2b) in mutually opposed directions; the linking means comprise an actuation member (5) and motion transmission means (10, 11), comprising a first and a second torsion bar (18, 19), capable of operatively engaging, at an end portion thereof, the actuation member (5) and, at the opposite end portion, the first and the second carriages (3, 4), respectively. The actuation member (5) is rotatably associable to the plate (2, 2a, 2b) at a section located approximately centrally relative to the first and second carriages (3, 4) and includes first effort reducing means (7, 9); the motion transmission means (10, 11) further include second effort reducing means (14, 15, 16, 17) adapted to engage the first effort reducing means (7, 9) and to be coupled to the first and second torsion bars (18, 19), respectively, so as to be integrally rotatable and freely longitudinally slidable relative to the first and second torsion bars (18, 19), respectively.

IPC 8 full level

A63C 9/00 (2006.01)

CPC (source: EP US)

A63C 9/003 (2013.01 - EP); **A63C 9/005** (2013.01 - EP US)

Citation (applicant)

- FR 2151666 A5 19730420 - SALOMON & FILS F
- DE 2246668 A1 19740411 - VER BAUBESCHLAG GRETSCH CO
- WO 03037452 A1 20030508 - SALOMON SA [FR], et al
- EP 0719166 A1 19960703 - MAGGIOLO MARCO [IT]

Citation (search report)

- [A] EP 1199090 A2 20020424 - MARKER DEUTSCHLAND GMBH [DE]
- [A] AT 9322 U1 20070815 - TYROLIA TECHNOLOGY GMBH [AT]
- [A] WO 0243822 A1 20020606 - BENETTON SPA [IT], et al
- [A] EP 1576990 A1 20050921 - TYROLIA TECHNOLOGY GMBH [AT]
- [A] EP 1645310 A1 20060412 - MARKER DEUTSCHLAND GMBH [DE]

Cited by

EP2923741A1; CN103189111A; US8910967B2; WO2012045723A1

Designated contracting state (EPC)

AT DE FR IT

Designated extension state (EPC)

AL BA RS

DOCDB simple family (publication)

EP 2082789 A1 20090729; EP 2082789 B1 20111207; AT E536208 T1 20111215; IT PN20080001 A1 20090726

DOCDB simple family (application)

EP 09150349 A 20090109; AT 09150349 T 20090109; IT PN20080001 A 20080125