

Title (en)  
ROTARY VANE MACHINE

Title (de)  
DREHSCHIEBERMASCHINE

Title (fr)  
MACHINE ROTATIVE À PALETTE COULISSANTE

Publication  
**EP 2090782 A4 20120307 (EN)**

Application  
**EP 07835023 A 20071002**

Priority  
• RU 2007000534 W 20071002  
• RU 2006138903 A 20061030

Abstract (en)  
[origin: EP2090782A1] The invention refers to mechanical engineering and can be used in rotor vane pumps, hydromotors, hydrostatic differentials and transmissions with increased efficiency at high pressure. The invention is aimed to improve insulation of a working chamber and force chambers of variable length in a wide range of deformations and tolerances as well as to improve efficiency at high pressure. A rotor vane machine consists of two units, a housing and a rotor installed with the possibility of reciprocal rotation. At least one of the two units is adaptive, that is it includes force chambers of variable length kinematically connecting the working and supporting parts of the adaptive unit with the possibility of their reciprocal axial displacements and tilts sufficient to provide a sliding insulating contact between the working parts of both units of the rotor vane machine during their reciprocal rotation, wherein the variation of the force chambers length is resulting in the mentioned reciprocal movements of the working and supporting parts of the adaptive unit. Every force chamber of variable length includes a force cavity hydraulically connected to the working chamber and the means of its insulation, including at least two moving elements installed with formation of sliding insulating contacts between the following pairs of the surfaces: between the insulating surface of one of the moving elements and the insulating surface of one of the parts of the adaptive unit, between the insulating surface of another moving element and the insulating surface of another part of the adaptive unit and between the insulating surfaces of the moving elements. At least in one of the contacts both insulating surfaces are cylindrical and at least in one of them they are spherical. Reciprocal sliding of cylindrical surfaces provides insulation during reciprocal axial movements of the working and supporting parts of the adaptive unit while reciprocal sliding of the spherical surfaces provides insulation during reciprocal tilted movements of the parts. To provide insulation during reciprocal transverse movements of these parts at least in one of other insulating contacts both insulating surfaces are either flat or spherical.

IPC 8 full level  
**F01C 1/344** (2006.01); **F01C 19/08** (2006.01)

CPC (source: EP US)  
**F03C 2/304** (2013.01 - EP US); **F04C 2/3448** (2013.01 - EP US); **F04C 15/0023** (2013.01 - EP US)

Citation (search report)  
• [XP] WO 2007032703 A1 20070322 - STROGANOV ALEXANDER ANATOLYEV I [RU], et al  
• [XP] WO 2006115434 A1 20061102 - STROGANOV ALEXANDER ANATOLYEV I [RU], et al  
• [X] US 3250223 A 19660510 - KRAWACKI MICHAEL J  
• [X] US 2957429 A 19601025 - FISK JAMES C  
• [A] EP 1536138 A1 20050601 - STROGANOV ALEXANDR ANATOLIEVIC [RU], et al  
• [A] EP 1293672 A1 20030319 - STROGANOV ALEXANDR ANATOLIEVIC [RU], et al  
• [A] DE 10200471 A1 20030710 - BITTEL KARL [DE]  
• [A] US 2977889 A 19610404 - FISK JAMES C  
• [A] EP 0269474 A1 19880601 - SULZER CONSTR MECAN [FR], et al  
• See references of WO 2008054244A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 2090782 A1 20090819; EP 2090782 A4 20120307**; CA 2667689 A1 20080508; CA 2667689 C 20160628; CN 101636587 A 20100127; CN 101636587 B 20120808; EA 013809 B1 20100830; EA 200900588 A1 20090828; RU 2327900 C1 20080627; UA 92685 C2 20101125; US 2011189045 A1 20110804; WO 2008054244 A1 20080508

DOCDB simple family (application)  
**EP 07835023 A 20071002**; CA 2667689 A 20071002; CN 200780048965 A 20071002; EA 200900588 A 20071002; RU 2006138903 A 20061030; RU 2007000534 W 20071002; UA A200905009 A 20071002; US 44778607 A 20071002