

Title (en)

OPTICAL TRANSMISSION ELEMENT HAVING HIGH TEMPERATURE STABILITY

Title (de)

OPTISCHES ÜBERTRAGUNGSELEMENT MIT HOHER TEMPERATURFESTIGKEIT

Title (fr)

ÉLÉMENT DE TRANSMISSION OPTIQUE À RÉSISTANCE ÉLEVÉE À LA TEMPÉRATURE

Publication

**EP 2095163 A1 20090902 (DE)**

Application

**EP 07857417 A 20071211**

Priority

- EP 2007063730 W 20071211
- DE 102006060431 A 20061220

Abstract (en)

[origin: WO2008074700A1] An optical transmission element (100) has a plurality of optical waveguides (10) which are arranged as a bundle and embedded into a filling composition (21). The optical waveguides (10) and the filling composition (21) are surrounded by a casing (30). A material composed of a resin which contains for example an acrylate enriched with a filler is used as materials for the casing. By mixing photoinitiators into the material composed of the resin of the casing (30), it is possible for the casing material of the casing to be cured by irradiation with ultraviolet light. Owing to the use of a material composed of resin during the production of the casing (30) of the optical transmission element, it is possible for thin casing layers to be produced at a high material processing speed.

IPC 8 full level

**G02B 6/44** (2006.01)

CPC (source: EP US)

**G02B 6/4436** (2013.01 - EP US); **G02B 6/4479** (2013.01 - EP US)

Citation (search report)

See references of WO 2008074700A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

**DE 102006060431 A1 20080626**; AU 2007336372 A1 20080626; EP 2095163 A1 20090902; US 2009257721 A1 20091015;  
WO 2008074700 A1 20080626

DOCDB simple family (application)

**DE 102006060431 A 20061220**; AU 2007336372 A 20071211; EP 07857417 A 20071211; EP 2007063730 W 20071211;  
US 48527309 A 20090616