

Title (en)  
TWO-FILAMENT LAMP

Title (de)  
ZWEIWEDELLELAMPE

Title (fr)  
AMPOULE À DEUX FILAMENTS

Publication  
**EP 2095399 B1 20160302 (DE)**

Application  
**EP 07857338 A 20071210**

Priority  
• EP 2007063618 W 20071210  
• DE 102006060419 A 20061220

Abstract (en)  
[origin: WO2008074684A2] Disclosed is a lamp, particularly for a vehicle headlight, comprising two spiral-wound filaments which are retained by three feeders within a bulb that is inserted into a base. The feeders are arranged on top of one another when the lamp is adequately oriented. A tail of the first spiral-wound filament is connected to a dimming cap, said tail being located at a distance from the base, while a tail of the second spiral-wound filament is connected to the central feeder, said tail being close to the base. The second filament tail that faces away and is located at a distance from the base is connected to the upper feeder. According to the invention, the lower feeder is connected to the dimming cap by means of an end, some sections of which are angled away from a longitudinal axis of the lamp.

IPC 8 full level  
**H01K 1/18** (2006.01); **H01K 1/40** (2006.01); **H01K 9/08** (2006.01)

CPC (source: EP US)  
**H01K 1/18** (2013.01 - EP US); **H01K 1/40** (2013.01 - EP US); **H01K 9/08** (2013.01 - EP US)

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**DE 102006060419 A1 20080626**; EP 2095399 A2 20090902; EP 2095399 B1 20160302; ES 2574833 T3 20160622; HU E028007 T2 20161128; US 2010039017 A1 20100218; US 8188658 B2 20120529; WO 2008074684 A2 20080626; WO 2008074684 A3 20090226

DOCDB simple family (application)  
**DE 102006060419 A 20061220**; EP 07857338 A 20071210; EP 2007063618 W 20071210; ES 07857338 T 20071210; HU E07857338 A 20071210; US 44833107 A 20071210