

Title (en)

METHOD AND APPARATUS FOR CONTROLLING EXHAUST TEMPERATURE OF A DIESEL ENGINE

Title (de)

VERFAHREN UND VORRICHTUNG ZUR STEUERUNG DER ABGASTEMPERATUR EINES DIESELMOTORS

Title (fr)

PROCÉDÉ ET APPAREIL POUR RÉGULER LA TEMPÉRATURE D'ÉCHAPPEMENT D'UN MOTEUR DIESEL

Publication

EP 2097630 A2 20090909 (EN)

Application

EP 07863026 A 20071214

Priority

- US 2007025787 W 20071214
- US 87679306 P 20061222

Abstract (en)

[origin: WO2008082492A2] An apparatus and method for cooling an exhaust gas flow of an internal combustion engine of a truck or other vehicle includes a conduit connected to an air source, for example, a turbo driven compressor to deliver air to the exhaust stack or tail pipe. The conduit is controlled by a valve, which is opened and closed by a controller responsive to a measured exhaust gas temperature above a threshold and a vehicle speed below a threshold. The invention is particularly advantageous for engine exhausts having aftertreatment devices that require high temperature regeneration.

IPC 8 full level

F02B 37/00 (2006.01); **F01N 3/021** (2006.01); **F01N 3/05** (2006.01)

CPC (source: EP US)

F01N 3/05 (2013.01 - EP US); **F01N 3/021** (2013.01 - EP US); **F01N 2270/02** (2013.01 - EP US); **F02B 37/00** (2013.01 - EP US);
F02D 41/0007 (2013.01 - EP US); **F02D 41/027** (2013.01 - EP US); **Y02T 10/12** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

WO 2008082492 A2 20080710; **WO 2008082492 A3 20081002**; **WO 2008082492 A4 20100429**; BR PI0720579 A2 20140204;
CN 101568703 A 20091028; CN 101568703 B 20120704; EP 2097630 A2 20090909; EP 2097630 A4 20110112; EP 2097630 B1 20160608;
JP 2010515847 A 20100513; JP 5289323 B2 20130911; US 2010043430 A1 20100225; US 8099953 B2 20120124

DOCDB simple family (application)

US 2007025787 W 20071214; BR PI0720579 A 20071214; CN 200780047854 A 20071214; EP 07863026 A 20071214;
JP 2009542847 A 20071214; US 44802107 A 20071214