

Title (en)

Device for sequentially moving at least two fluid-actuated displacement devices

Title (de)

Einrichtung zur Sicherung der Bewegungsreihenfolge von zumindest zwei fluidbetätigten Verdrängereinheiten

Title (fr)

Dispositif pour séquentiellement déplacer au moins deux vérins actionnés par fluide

Publication

EP 2101066 B1 20140716 (DE)

Application

EP 09002042 A 20090213

Priority

DE 102008013765 A 20080312

Abstract (en)

[origin: EP2101066A2] The device has a primary unit laterally moved in front of a secondary unit, where the secondary unit is designed as a hydraulic cylinder (1) with a piston rod (3) moved in and out to/from a cylinder tube (2). The hydraulic cylinder has a piston base-side pressurizing medium chamber (A), which is connected with a pressurizing medium inlet (10) for the hydraulic cylinder, and a piston rod-side pressurizing medium chamber (B). A valve device (15) controls discharge of a pressurizing medium from the piston rod-side pressurizing medium chamber.

IPC 8 full level

F15B 11/20 (2006.01); **F15B 15/14** (2006.01); **F15B 15/20** (2006.01)

CPC (source: EP)

B66F 9/22 (2013.01); **F15B 11/205** (2013.01); **F15B 15/1457** (2013.01); **F15B 15/149** (2013.01); **F15B 15/204** (2013.01)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 2101066 A2 20090916; **EP 2101066 A3 20130220**; **EP 2101066 B1 20140716**; DE 102008013765 A1 20090917

DOCDB simple family (application)

EP 09002042 A 20090213; DE 102008013765 A 20080312