

Title (en)  
ANCHOR POINT FOR A LIFT ASSEMBLY

Title (de)  
AUFZUGSMONTAGEANKER

Title (fr)  
POINT D'ANCRAGE POUR ASCENSEUR

Publication  
**EP 2110486 B1 20200325 (DE)**

Application  
**EP 09005209 A 20090409**

Priority  
CH 5912008 A 20080416

Abstract (en)  
[origin: EP2110486A2] The anchor has a suspending section (6a) for suspending shackle, hook or ropes, and an anchoring section molded into a concrete floor (3). The suspending section is arranged in a recess unit (2) that is provided adjacent to a lower casing (4) for molding into the concrete floor and generates a hollow space (1) adjacent to a lower side of a cover, where the hollow space is enclosed in the floor after removing the suspending section. The recess unit is made of foamed plastic and has a length of 15 to 20 centimeter. The recess unit comprises a wall made of metal or plastic.

IPC 8 full level  
**E04B 1/41** (2006.01); **B66C 1/66** (2006.01); **E04G 21/14** (2006.01)

CPC (source: CH EP)  
**B66B 7/08** (2013.01 - EP); **B66B 11/0005** (2013.01 - CH EP); **E04B 1/4142** (2013.01 - CH EP); **E04G 15/04** (2013.01 - EP);  
**E04B 2001/4192** (2013.01 - EP)

Cited by  
CN106049883A; CN105370033A; EP2407612A3; DE102016118883A1; EP2913458A1; FR3018087A1; DE202010010127U1; EP2407612A2; WO2013064497A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 2110486 A2 20091021; EP 2110486 A3 20121003; EP 2110486 B1 20200325; CH 718496 B1 20221014**

DOCDB simple family (application)  
**EP 09005209 A 20090409; CH 5912008 A 20080416**