

Title (en)

Device preventing false handling and locking fitting of the sash bolt or sash bolt-lock type for a sliding window

Title (de)

Vorrichtung zur Verhinderung von Fehlbedienung und Treibstangenverriegelungsbeschlag für eine Schiebetür

Title (fr)

Dispositif d'anti-fausse manoeuvre et ferrure de verrouillage de type cremone ou cremone-serrure pour ouvrant coulissant

Publication

**EP 2112303 B1 20100616 (FR)**

Application

**EP 09305341 A 20090421**

Priority

FR 0852702 A 20080422

Abstract (en)

[origin: EP2112303A1] The device has a locking finger (13) that is displaced at a rear side of a handling rod (10) along a direction perpendicular to the rod and moved to a locking position of the rod by an elastic return unit (15) e.g. helical spring. The finger is prolonged by a sensor (17) extended at a front side of the rod to push the finger to an unlocking position during closing a sliding opening frame. The finger is prolonged at the rear side of the rod by a pre-positioning end-fitting (25) co-operating with an opening on the frame to assure positioning of an espagnolette or espagnolette lock on the frame. An independent claim is also included for an espagnolette or espagnolette lock type lock fitting for a sliding opening frame, comprising a handling rod.

IPC 8 full level

**E05B 63/18** (2006.01)

CPC (source: EP)

**E05B 63/185** (2013.01); **E05C 9/026** (2013.01); **E05B 65/08** (2013.01)

Cited by

GB2527500A; GB2527500B; CN114776449A

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 2112303 A1 20091028; EP 2112303 B1 20100616**; AT E471424 T1 20100715; DE 602009000043 D1 20100729; ES 2347504 T3 20101029; FR 2930273 A1 20091023; FR 2930273 B1 20100423

DOCDB simple family (application)

**EP 09305341 A 20090421**; AT 09305341 T 20090421; DE 602009000043 T 20090421; ES 09305341 T 20090421; FR 0852702 A 20080422