

Title (en)

USES OF FUEL COMPOSITION FOR DIESEL ENGINES

Title (de)

VERWENDUNG VON BRENNSTOFFZUSAMMENSETZUNG FÜR DIESELMOTOREN

Title (fr)

UTILISATION DES COMPOSITIONS DE CARBURANT POUR MOTEURS DIESEL

Publication

**EP 2118243 A1 20091118 (EN)**

Application

**EP 08709234 A 20080227**

Priority

- EP 2008052348 W 20080227
- JP 2007049386 A 20070228

Abstract (en)

[origin: WO2008104556A1] A fuel composition for diesel engines comprising: (1) 80 to 0 % volume of one or more intermediate fractions selected from the group consisting of a straight-run kerosene fraction, a straight-run light oil fraction, a cracked light oil fraction, a cracked kerosene fraction and hydrodesulphurised products of these; and (2) 20 to 100 % volume of gas-to-liquid product, wherein, in a test of oxidation stability in accordance with the EN14112 test, the time until a change of electrical conductivity occurs at a liquid temperature of 150 °C is at least four hours.

IPC 8 full level

**C10L 1/183** (2006.01); **C10L 1/08** (2006.01); **C10L 1/223** (2006.01); **C10L 10/00** (2006.01)

CPC (source: EP US)

**C10L 1/08** (2013.01 - EP US); **C10L 1/1832** (2013.01 - EP US); **C10L 1/223** (2013.01 - EP US); **C10L 10/00** (2013.01 - EP US)

Citation (search report)

See references of WO 2008104556A1

Citation (examination)

JP 2004359856 A 20041224 - IDEMITSU KOSAN CO

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

**WO 2008104556 A1 20080904**; AR 065487 A1 20090610; EP 2118243 A1 20091118; JP 2008214369 A 20080918;  
SG 10201705367X A 20170728; US 2008256846 A1 20081023

DOCDB simple family (application)

**EP 2008052348 W 20080227**; AR P080100795 A 20080227; EP 08709234 A 20080227; JP 2007049386 A 20070228;  
SG 10201705367X A 20080227; US 3777308 A 20080226